



5V0-21.21^{Q&As}

VMware HCI Master Specialist Dumps

Pass VMware 5V0-21.21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/5v0-21-21.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Upon checking the latency goal under vSAN performance diagnostics, the vSAN Administrator sees this message displayed:

The increase in latency in the vSAN stack might be beyond expected limits.

Which two root causes can be identified to help remediate the issue? (Choose two.)

- A. vSAN VMKernel portgroup is configured with the "Route based on IP hash" teaming policy
- B. vSAN encryption is enabled
- C. Large packet losses and retransmissions on the network layer
- D. Incorrect sizing of the disk groups capacity disks
- E. One or more disk groups are congested

Correct Answer: CE

Reference: <https://kb.vmware.com/s/article/2150018>

QUESTION 2

An administrator wants to deploy a desktop and application virtualization solution on top of vSAN. Which VMware product should the administrator install?

- A. VMware Dynamic Environment Manager
- B. VMware Horizon Apps
- C. VMware Workspace One Access
- D. VMware Horizon

Correct Answer: D

QUESTION 3

A 4-node vSAN cluster is configured with an erasure coding storage policy. The Ensure Accessibility maintenance mode was selected. While performing the maintenance, a second node fails.

What will be the impact on the vSAN cluster?

- A. There will be no impact on performance.
- B. The VMs will no longer be accessible.



- C. The performance will be degraded.
- D. The VMs will be in a suspended state.

Correct Answer: A

Reference: <https://docs.vmware.com/en/VMware-vSphere/6.7/com.vmware.vsphere.virtualsan.doc/GUID521EA4BC-E411-47D4-899A-5E0264469866.html>

QUESTION 4

A customer is planning to deploy a vSAN cluster to host their in-house distributed ERP system. The hardware specifications for their server nodes include:

2 x Intel Xeon CPU E5-2697 v3 @ 2.60GHz 1TB memory

Which boot device is supported for the vSAN ESXi nodes for this customer?

- A. A 16GB single-level cell (SLC) SATADOM device must be used.
- B. A 4GB USB or SD device must be used.
- C. A 16GB multiple-level cell (MLC) SATADOM device must be used.
- D. ESXi Hosts must boot from a PMEM device.

Correct Answer: C

QUESTION 5

During a design workshop for a stretched vSAN cluster, the requirement that some of the VMs be configured with no-mirror between sites was discussed.

Which three recommendations should the architect provide to address an event of a network partition between two sites? (Choose three.)

- A. Host isolation response must exclude the VMs required
- B. The default gateway must be used as the only isolation address
- C. One of isolation addresses should reside in the site 1 data center
- D. VMware vSphere DRS rules to force the VMs to run where the data resides
- E. One isolation address reachable only from the witness appliance in both sites
- F. One of isolation addresses should reside in the site 2 data center

Correct Answer: ADF



VCE & PDF

GeekCert.com

<https://www.geekcert.com/5v0-21-21.html>

2024 Latest geekcert 5V0-21.21 PDF and VCE dumps Download

[5V0-21.21 Practice Test](#)

[5V0-21.21 Study Guide](#)

[5V0-21.21 Exam Questions](#)