



# 5V0-21.21<sup>Q&As</sup>

VMware HCI Master Specialist Dumps

**Pass VMware 5V0-21.21 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/5v0-21-21.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by VMware  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

An administrator of “vsan-prod” cluster noticed the witness components of VMs are flagged as absent after a failed attempt to replace the vSAN Witness Host.

Which action should the administrator take to resolve this issue?

- A. Upgrading the vSAN on-disk format
- B. Running the vSAN Skyline Health check to ensure there are vSAN Object Health errors and executing the Repair Object Immediately option
- C. Using the RVC command: `vsan.resync_dashboard ~/computers/vsan-prod`
- D. Placing the vSAN Witness Host in Maintenance Mode and adding to the vSAN cluster

Correct Answer: D

Reference: <http://vcallaway.com/wp-content/uploads/2018/05/VMware%C2%AE-vSAN%E2%84%A2Design-and-Sizing-Guide-6.5.pdf>

---

### QUESTION 2

A cache disk failure marked a vSAN disk group as failed, and the data is being rebuilt on other disk groups.

Which action should the vSAN administrator take to reduce the negative impact on the VMs?

- A. Enabling Resync Throttling
- B. Enabling Maintenance mode with no data evacuation
- C. Enabling automatic rebalance
- D. Setting the vSAN policy's IOPS limit for object value to 0 (unlimited)

Correct Answer: A

### QUESTION 3

During a maintenance action on a vSAN node, a vSAN administrator noticed that the default repair delay time is about to be reached.

Which two commands must be run to extend the time? (Choose two.)

- A. `/etc/init.d/vsanmgmt restart`
- B. `esxcli system settings advanced set -o /VSAN/ClomRepairDelay -i 50`
- C. `esxcli system settings advanced set -o /VSAN/ClomRepairDelay -i 80`



D. /etc/init.d/clomd restart

E. /etc/init.d/vsanobserver restart

Correct Answer: CD

Reference: <https://kb.vmware.com/s/article/2075456>

---

#### QUESTION 4

A customer has upgraded to vSAN 7, but there is still an existing legacy host which must be removed from the vSAN cluster.

Which three steps must an administrator take to successfully remove this host from the vSAN cluster? (Choose three.)

A. Place the host in maintenance mode with Ensure Accessibility

B. Disconnect from vCenter Server

C. Place the host in maintenance mode with Full Data migration

D. Place the host in maintenance mode with no data migration

E. Remove from vSAN cluster

F. Delete the disk group(s) on the legacy host

Correct Answer: CEF

Reference: <http://www.vexpertconsultancy.com/2019/06/step-by-step-remove-a-node-permanently-from-avsan-cluster/>

---

#### QUESTION 5

An administrator has an absent capacity disk.

Which action, if any, should the administrator take to resolve the problem?

A. Wait, and vSAN will rebuild it.

B. Replace the faulty disk.

C. Replace the faulty host.

D. Verify the host is not isolated.

Correct Answer: A