600-212^{Q&As}

mplementing Cisco Service Provider Mobility LTE Networks

Pass Cisco 600-212 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/600-212.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Drag the protocol on the left to the node on the right that it runs between.	
GTP-U	eNodeB and MME
NAS	HSS and MME
Diameter	eNodeB and SGW
S1-AP	UE and MME

Select and Place:

Drag the protocol on the left to the node on the right that it runs between.	
GTP-U	eNodeB and MME
NAS	HSS and MME
Diameter	eNodeB and SGW
S1-AP	UE and MME

Correct Answer:

Drag the protocol on the left to the node on the right that it runs between.	
	S1-AP
	Diameter
	GTP-U
	NAS

QUESTION 2

Which two IEs are ignored by the LTE domain when the EPS QoS parameter is mapped to the R99 QoS parameter? (Choose two.)

A. pre-emption capability

B. ARP priority

C. MBR of PDP context associated with the background traffic class

D. MBR of PDP context associated with the interactive traffic class

E. pre-emption vulnerability

Correct Answer: AE

QUESTION 3

You are configuring the Cisco ASR 5000 Serving Gateway. You want to configure a reference point between the eNodeB and the SGW for the user plane and inter-eNodeB path switching during handover. Which option describes where the interface IP address associates?

A. The address associates to the SGW service.

B. The address associates to the GTPU service.

C. The address associates to the EGTP service.

D. The address associates to the S1U service.

Correct Answer: B

QUESTION 4

Which network function converts Voice over LTE voice bearer to PSTN voice bearer?

A. border gateway control function

B. media gateway function

C. multimedia resource function

D. session border controller function

Correct Answer: B

QUESTION 5

The IP pools that are configured on the Cisco ASR 5000 are used for address allocation. AAA and DHCP have not been enabled from the PGW. Which two parameters does the Cisco ASR 5000 PGW use to generate the subscriber ID for IP address allocation? (Choose two.)

A. IMEI

B. MSISDN

C. EPS bearer ID

D. IMSI

E. username

Correct Answer: DE