



# 600-212<sup>Q&As</sup>

Implementing Cisco Service Provider Mobility LTE Networks

## Pass Cisco 600-212 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/600-212.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Which Diameter command is used when P-CSCF sends the desired uplink and downlink bandwidth information to the PCRF?

- A. RAR
- B. AAR
- C. CCR
- D. MAR

Correct Answer: B

---

### QUESTION 2

Which capability does trace logging on the Cisco ASR 5000 enable the operator to do?

- A. enables debug-level temporary logging filters based on call ID, IP address, MSID, or username
- B. enables logging for all management messages based on call ID, IP address, MSID, or username
- C. enables syslog facility logging for debug-level messages related to call management messaging
- D. enables informational-level syslog facility logging for call management messaging

Correct Answer: A

---

### QUESTION 3

Which three configuration options do local-user accounts allow for on the Cisco ASR 5000? (Choose three.)

- A. max failed logins
- B. password complexity
- C. lockout times
- D. administrator level
- E. username complexity
- F. context access

Correct Answer: ABC

---

### QUESTION 4



---

Which MME feature can be configured in the call control policy on the Cisco ASR 5000 system?

- A. super-charger feature configuration
- B. sgtp-service association
- C. direct-tunnel feature configuration
- D. RAT frequency selection priority override

Correct Answer: D

---

#### QUESTION 5

Which two options are two functions of a proxy CSCF? (Choose two.)

- A. a SIP registrar that is responsible for session management
- B. an entity in IMS that connects with the ENUM server for the number portability function
- C. a SIP proxy node that acts as a signaling entry point into IMS
- D. an entity in IMS that works on both signaling and bearer domain
- E. an entity in IMS that connects with PCRF via the Rx interface
- F. an entity in IMS that interacts with application servers

Correct Answer: CE

[600-212 PDF Dumps](#)

[600-212 Exam Questions](#)

[600-212 Braindumps](#)