https://www.geekcert.com/642-874.html
GeekCert.com

642-874^{Q&As}

Designing Cisco Network Service Architectures

Pass Cisco 642-874 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/642-874.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

The network designer needs to consider the number of multicast applications and sources in the network to provide the most robust network possible. Which of the following is a consideration the designer must also address?

A. The IGPs should utilize authentication to avoid being the most vulnerable component

B. With SSM source or receiver attacks are not possible

C. With Shared Trees access control is always applied at the RP

D. Limit the rate of Register messages to the RP to prevent specific hosts from being attacked on a PIM- SM network

Correct Answer: B

QUESTION 2

Which practice is recommended when designing scalable OSPF networks?

A. Maximize the number of routers in an area.

B. Minimize the number of ABRs.

C. Minimize the number of areas supported by an ABR.

D. Maximize the number of router adjacencies.

Correct Answer: C

QUESTION 3

Which two of these are characteristics of multicast routing? (Choose two.)

A. multicast routing uses RPF.

B. multicast routing is connectionless.

C. In multicast routing, the source of a packet is known.

D. When network topologies change, multicast distribution trees are not rebuilt, but use the original path

E. Multicast routing is much like unicast routing, with the only difference being that it has a a group of receivers rather than just one destination

Correct Answer: AC

QUESTION 4

Which three options are features of IP SLAs? (Choose three.)

A. enables verification of service guarantees

B. dynamically adjusts QoS parameters

C. validates network performance and metrics

D. initiates failover for saturated links

E. proactively identifies network related issues

Correct Answer: ACE

QUESTION 5

A company implemented VoIP in a campus network and now wants a consistent method to implement using AutoQoS. Which two parameters must be considered before AutoQoS is configured? (Choose two.)

A. CEF must be enabled.

B. AutoQoS is available only on routers.

C. Traffic discovery must be performed manually.

D. No service policy can be applied already.

E. Manual traffic analysis must be performed.

Correct Answer: AD

[Latest 642-874 Dumps](#)   [642-874 Study Guide](#)   [642-874 Braindumps](#)

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.geekcert.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: