



642-889^{Q&As}

Implementing Cisco Service Provider Next-Generation Edge Network Services

Pass Cisco 642-889 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/642-889.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

When troubleshooting EoMPLS configuration problems, which three parameters must match between the two ends of the pseudowire configurations? (Choose three.)

- A. control word usage
- B. MTU size
- C. pseudowire ID
- D. Xconnect group name
- E. EFP subinterface number

Correct Answer: ABC

Provisioning an AToM Static Pseudowire

In this configuration task, you use options in the xconnect Ethernet interface configuration command to specify a static connection, and mpls commands in xconnect mode to statically set the following pseudowire parameters:

QUESTION 2

Which two statements about implementing a separate MPLS VPN to provide customers Internet access are correct? (Choose two.)

- A. The Internet gateway router will act as a CE router.
- B. Customers will use separate interfaces for VPN and Internet access.
- C. Customers are assigned to the Internet VPN.
- D. Internet routes will be leaked from the PE global routing table to the customer VRF.

Correct Answer: AC

QUESTION 3

Which three commands represent valid QoS classifiers of traffic in case of an EoMPLS circuit? (Choose three.)

- A. match cos
- B. match mpls experimental
- C. match qos-group
- D. match fr-de
- E. match protocol



F. match ip address prefix-list

G. match tag

Correct Answer: ABC

QUESTION 4

Which two protocols can be used for VPLS signaling on a Cisco IOS XR router? (Choose two.)

A. BGP

B. LDP

C. TDP

D. RSVP

E. PBB

Correct Answer: AB

QUESTION 5

When implementing EoMPLS on Cisco IOS XR routers, which command under the l2vpn configuration mode is used to define the pseudowire?

A. pbb

B. xconnect

C. connect

D. bridge

E. bridge-domain

Correct Answer: B

[642-889 PDF Dumps](#)

[642-889 VCE Dumps](#)

[642-889 Braindumps](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

- 100% Guaranteed Success
- 100% Money Back Guarantee
- 365 Days Free Update
- Instant Download After Purchase
- 24x7 Customer Support
- Average 99.9% Success Rate
- More than 800,000 Satisfied Customers Worldwide
- Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.geekcert.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.
All trademarks are the property of their respective owners.
Copyright © geekcert, All Rights Reserved.