



# 7004.1<sup>Q&As</sup>

Avaya Communication Server 1000 for Avaya Aura® Maintenance Exam

## Pass Avaya 7004.1 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/7004-1.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





## QUESTION 1

Click the Exhibit button.

0	Attendant	TRAN	AC1	TRAN	AC2
1	SPRE Code				
20XX-29XX	Trunk Access Codes	NPA	1867	XXX	232
3XXX	DID DNs	RLI	4	RLI	1
4XXX	Non-DID DNs	SDRR	NONE	SDRR	NONE
5		ITEI	NONE	ITEI	NONE
6					
7		NPA	1914	XXX	234
8	AC1	RLI	3	RLI	0
9	AC2	SDRR	NONE	SDRR	NONE
		ITEI	NONE	ITEI	NONE
		NPA	1718	XXX	237
		RLI	4	RLI	1
		SDRR	NONE	SDRR	NONE
		ITEI	NONE	ITEI	NONE
		NPA	1717	XXX	343
		RLI	9	RLI	0
		DENY	39680	SDRR	NONE
		DENY	39681	ITEI	NONE
		DID	3344000		
				XXX	421
		NPA	1967	RLI	1
		RLI	4	SDRR	NONE
		SDRR	NONE	ITEI	NONE
		ITEI	NONE		
		NPA	1902		
		RLI	2		
		DID	33330		
		ITEI	NONE		

Refer to the customer's dialing plan and programming show in the exhibits. Assuming all required Route List Indexes have been programmed, why will the station user's dialed call of 8-1-717-398-8001 not complete?

- A. AC2 Access Code was not dialed
- B. NPA1717 is not provisioned in the customer's database
- C. 398-8001 would be denied under the SDRR programming
- D. AC1 Access Code was not dialed

Correct Answer: C


## QUESTION 2

Click the Exhibit button.



Managing: EM on co-res-cppm(172.16.100.30)  
Phones > Phone Details

### Phone Details

 System: EM on co-res-cppm  
Phone Type: 1140  
Sync Status: TRN

General Properties | Features | Keys | User Fields

Custom View: All

Feature	Description	Value
CCBA	Collect Call Blocking	Denied
CCSA	Controlled Guest Telephone	Denied
CDCA	Conferee Display Count	Conferee Display Count Allowed
CDEN	Card Density	Octal Density
CDMI	Converged Desktop Multimedia Service	CDM Denied
CDMA	External Station Activity Records	Denied
CFHA	Call Forward/Hunt Override	Denied
CFTA	Call Forward by Call Type	Denied
CFXA	Call Forward External	Denied
CLBA	Calling Party Privacy	Denied
CLRO	Calling Number Restriction Override	Denied
CLS	Trunk/Call Type Access Restriction	Toll Denied
CLTA	Network Call Trace	Denied
CNDA	Call Party Name Display	Denied
CNIA	Call Number Information	Denied
CNTA	Network ACD Countdown	Denied

You manage a Communication Server 1000 RIs. 7 x system at a customer site. The customer reports that extension 2000 cannot make an unassisted long distance calls. With reference to the exhibit, which feature is restricting the user?

- A. CCBA
- B. CCSA
- C. CLRO
- D. CLS

Correct Answer: D



### QUESTION 3

Click the Exhibit button.

**Customer 0, Route 8 Property Configuration**

**- Basic Configuration**

Route data block (RDB) (TYPE)	ACD
Customer number (CUST)	00
Route number (ROUT)	8
Designator field for trunk (DES)	
Trunk type (TKTP)	OUT
Incoming and outgoing trunk (ICOG)	Outgoing only Trunk (OGT) ▼
Access code for the trunk route (ACOD)	4848
The route is for a virtual trunk route (VTRK)	<input type="checkbox"/>
- Zone for codec selection and bandwidth management (ZONE)	00006 (0 - 8000)
- Node ID of signaling server of this route (NODE)	1100 (0 - 9999)
Calling number dialing plan (CHDP)	Unknown (UKN) ▼

**• Basic Route Options**  
**• Network Options**  
**• General Options**  
**• Advanced Configurations**

You are asked to review the existing route information for the customer. According to the printout shown in the exhibit, which type of route is this?

- A. a directinward dialroute
- B. amedia services route
- C. an integrated services digital network route
- D. an incoming only route

Correct Answer: A

### QUESTION 4

A customer has a Communication Server 1000 RIs. 7 x system at their site. You have been asked to add the Call Pickup feature to the ten IP telephones in the sales department. The customer wants to be sure active calls are not lost when the change are made. Which Phones Configuration feature can be enabled allowed you to ensure changes to the telephones are not transmitted to the call server until the telephone is not busy?

- A. Bulk change



- B. Courtesy change
- C. Group change
- D. Template change

Correct Answer: B

---

#### QUESTION 5

You are configuring a bandwidth management zone on a Communication Server 1000 RIs. 7 x Call Server.

The Call Server zones will be used for interface communications between endpoints (IP telephones and gateways).

Which is the preferred bandwidth management strategy, assuming the network has adequate bandwidth?

- A. Best Quality (BQ)
- B. Best Bandwidth (BB)
- C. Allocated Bandwidth (AB)
- D. Best Effort (BE)

Correct Answer: A

[7004.1 VCE Dumps](#)

[7004.1 Practice Test](#)

[7004.1 Exam Questions](#)