



71800X^{Q&As}

71800X - Avaya IX Messaging Implementation and Maintenance

Pass Avaya 71800X Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/71800x.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

When using distributed VSN configuration, how many advanced users can an entire Avaya IX™ Messaging solution support?

- A. 4,800 advanced users
- B. 20,000 advanced users
- C. 60,000 advanced users
- D. 80,000 advanced users

Correct Answer: D

QUESTION 2

In Avaya IX™ Messaging High Availability installations, on which servers are TLS configurations to be applied to secure the communication with the PBX(s)?

- A. Primary server only
- B. Primary server and all Secondary servers
- C. Primary server and Consolidated server
- D. Consolidated server only

Correct Answer: B

QUESTION 3

Which two prerequisites and considerations must be met prior installing Avaya IX™ Messaging? (Choose two.)

- A. Antivirus software must be installed and operating according to specifications.
- B. The corporate telephone system and PBX must be installed and functioning properly.
- C. The server must have the operating system installed, patched and completely updated.
- D. Create all accounts on the server locally, and it doesn't need to have any domain accounts provisioned.

Correct Answer: AD

QUESTION 4

The number of Content Sync Engine (CSE) Servers required depends upon the number of advanced users that will be working on the system. What kind of server is required for 2,500 Advanced users, in a High Availability solution?



- A. CSE Running on CS
- B. CSE Running on Backup Server
- C. CSE Running on Voice Server
- D. A dedicated CSE Server

Correct Answer: D

QUESTION 5

Which three requirements must be met for an Avaya IXTM Messaging High Availability installation? (Choose three.)

- A. Maximum round-trip latency between the voice servers and the PBX must not exceed 200 milliseconds. Optimal round-trip latency is less than 150 milliseconds.
- B. All servers must be part of the same Windows domain.
- C. All servers must have a minimum 1 Gb/s connection to the network.
- D. Maximum round-trip latency between the voice servers and the consolidated servers must not be more than 50 milliseconds.
- E. The path of connectivity must have 2 Mb/s guaranteed bandwidth with no steady-state congestion.

Correct Answer: BCE

[71800X VCE Dumps](#)

[71800X Practice Test](#)

[71800X Braindumps](#)