75940X^{Q&As}

Avaya Converged Platform Integration

Pass Avaya 75940X Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/75940x.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Using VMware networking in ACP 4200, how are Virtual NICs mapped to physical NICs?

A. Via DRS rules

B. On a 1-to-1 basis

C. Via Virtual Switches and Port Groups

D. Via the VNIIC mapping tables

Correct Answer: D

QUESTION 2

An installation engineer is installing the power connections to the ACP 4200.

What must the installation engineer be aware of?

A. Before connecting the power, the power switches of all components in the rack must be in the OFF position.

B. Power cables must only access the rack from the top of the rack.

C. Power connections must be within 10 feet (3 meters) of the rack.

D. Power cables must only access the rack from the bottom of the rack.

Correct Answer: A

QUESTION 3

Which application can a technician use to remotely connect to the Management Server Console on an ACP 4200?

A. VNC

B. Remote Desktop Connection

C. PuTTY

D. Team Viewer

Correct Answer: B

Reference: https://downloads.avaya.com/css/P8/documents/101054946

QUESTION 4

Which two statements about the HP Nimble storage systems used in ACP 4200 are true? (Choose two.)

A. ACP 4200 may use the HP Nimble 33 Base unit with up to 2 Expansion units.

B. ACP 4200 may use the HP Nimble 16 Base unit with up to 5 Expansion units.

C. ACP 4200 may use the HP Nimble 16 Base unit with up to 2 Expansion units.

D. ACP 4200 may use the HP Nimble 33 Base unit with up to 5 Expansion units.

Correct Answer: AB

QUESTION 5

What is a benefit of using Virtual Router Redundancy Protocol (VRRP) on the VSP switches in the ACP 4200?

A. It creates virtual Layer 2 connections for the VMs.

B. It allows you to connect to the switches for management access.

C. It ensures the end systems do not need to change their gateway IP address in the event of a fail-over.

D. It allows the end systems to automatically change their gateway IP address in the event of a fall-over.

Correct Answer: D

Reference: https://www.alliedtelesis.com/en/documents/vrrp-feature-overview-and-configuration-guide

[75940X Study Guide](#)   [75940X Exam Questions](#)   [75940X Braindumps](#)