



C4090-454^{Q&As}

IBM High-End Tape Technical Solutions V7

Pass IBM C4090-454 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/c4090-454.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A customer has installed two TS7700 Virtualization Engines in a grid configuration for disaster recovery. Cluster U is local to the production hosts, and Cluster 1 is located in the remote DR center with no host processors. They want to maximize the probability that recently written logical volumes are in the cache of Cluster 1 in case of a loss of Cluster U, while maintaining copies in both clusters. Which Copy Consistency Point settings are most appropriate to use?

- A. Cluster U = RD. Cluster 1 = RD
- B. Cluster U = RD. Cluster 1 = NR
- C. Cluster U = DR. Cluster 1 = DR
- D. Cluster U = NR, Cluster 1 = RN

Correct Answer: C

QUESTION 2

A customer wants to double the capacity and throughput capability of the existing TS3510 Tape Library. The available free space in the data center is limited so 324 frames must be included in the proposal. Which fact must the technical specialist take into account in order to meet the customer requirements?

- A. 324 frames do not provide the option for adding tape drives
- B. 324 frames cannot be placed at either end of the tape library
- C. 324 frames provide 2.5 times more cartridge slots compared to D frames
- D. 324 frames offer reduced `amounts per hour` when using cartridges in tiers 0 and 1

Correct Answer: A

QUESTION 3

What copying activity does "Pull Cache Copy Throttling" limit on the TS7740?

- A. the data copied from tape to cache
- B. the data copied from cache onto tape
- C. the data copied into the cache from another TS7740 cluster
- D. the data copied out from the cache into another TS7740 cluster

Correct Answer: C



QUESTION 4

Which of the following is a point of information output from VEHSTATS?

- A. The active data distribution
- B. The percentage cache hit rate
- C. The usage of specific stacked volume cartridge
- D. The use of TS7700 resources of a batch job or subsystem

Correct Answer: B

QUESTION 5

A banking customer's TS7740 was unable to replicate the tape backup data to the DR data center via the current grid network. The IBM support engineer had created a PMR with Severity 1 because the tape library is supporting the customer's production environment. Six hours after the PMR was created, IBM Level 2 support requested to change the Severity Level to 2, even though the problem had not been resolved. Based on IBM guidelines, why would this problem need to be reduced to Severity 2?

- A. Severity 1 only applies to Tape Failure
- B. Severity 1 only applies to Network Failure
- C. Severity 1 only applies to Production Failure
- D. Severity 1 problem must be resolved within 6 hours

Correct Answer: C

[C4090-454 VCE Dumps](#)

[C4090-454 Study Guide](#)

[C4090-454 Exam Questions](#)