



C4090-454^{Q&As}

IBM High-End Tape Technical Solutions V7

Pass IBM C4090-454 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/c4090-454.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which of the following is a point of information output from VEHSTATS?

- A. The active data distribution
- B. The percentage cache hit rate
- C. The usage of specific stacked volume cartridge
- D. The use of TS7700 resources of a batch job or subsystem

Correct Answer: B

QUESTION 2

With TS1140 drives, if host software is used to compress the data before sending it to the drive, then:

- A. The drive will determine if the data should be compressed
- B. The drive data compression must be disabled to avoid performance issues
- C. The drive data compression must be disabled to avoid expansion of the data
- D. The Data Class parameter COMPACTION=YES must be set to optimize compression

Correct Answer: A

QUESTION 3

A customer has an installed TS3SOO Tape Library with one L23 frame with only four TS1140 model drives. All are currently attached to open systems servers. The library and drives are being moved to another location and attached to a local

z/OS system.

Which additional hardware is essential at the new location to support four TS1140 drives?

- A. 3953-F05 with 3592-007
- B. 3952-F05 with 3592-007
- C. 3953-F05 with L05 Library Manager
- D. 3584-D23 with one Fibre Channel switch

Correct Answer: B



QUESTION 4

A service provider has two separate customers on different LPARS using a TS7740 and wants to ensure that neither customer can access the other customer's data from the host. Which of the following features, functions or processes would be recommended to achieve this?

- A. Use IODF and SDAC to prevent access to volume ranges by Libport ID
- B. Create separate partitions within the TS7700 using the categories defined in the DEVSUP member
- C. The functions DAA and SAA will work with JES2 on z/OS to direct workloads to the correct cluster
- D. Create separate physical cartridge pools so each customer's data resides on a different cartridge range

Correct Answer: A

QUESTION 5

A customer has installed a new TS7740 with 4 TB cache, 2 performance increments and 4 backend TS1140 drives. VEHSTATS shows that the TS7740 is experiencing pre-migrate throttling during the overnight batch run. What is the correct course of action?

- A. Review the effect of throttling and the PMTHLVL value with the customer
- B. Advise the customer to purchase an extra 2 TS1140 drives to relieve the throttling
- C. Advise the customer to purchase an extra 1 TB cache increment to relieve the throttling
- D. Advise the customer to purchase an extra performance increment to relieve the throttling

Correct Answer: A