



CCB-400^{Q&As}

Cloudera Certified Specialist in Apache HBase

Pass Cloudera CCB-400 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ccb-400.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cloudera
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

You want to do a full table scan on your data. You decide to disable block caching to see if this improves scan performance. Will disabling block caching improve scan performance?

- A. No. Disabling block caching does not improve scan performance.
- B. Yes. When you disable block caching, you free up that memory for other operations. With a full table scan, you cannot take advantage of block caching anyway because your entire table won't fit into cache.
- C. No. If you disable block caching, HBase must read each block index from disk for each scan, thereby decreasing scan performance.
- D. Yes. When you disable block caching, you free up memory for MemStore, which improves scan performance.

Correct Answer: B

QUESTION 2

You are storing page view data for a large number of Web sites, each of which has many subdomains (www.example.com, archive.example.com, beta.example.com, etc.) Your reporting tool needs to retrieve the total number of page views for a given subdomain of a Web site. Which of the following row keys should you use?

- A. The reverse domain name (e.g., com.example.beta)
- B. The domain name followed by the URL
- C. The URL
- D. The URL followed by the reverse domain name

Correct Answer: C

QUESTION 3

You need to create a "WebLogs" table in HBase. The table will consist of a single Column Family called "Errors" and two column qualifiers, "IP" and "URL". The shell command you should use to create the table is:

- A. `create 'WebLogs', {NAME => 'Errors:IP', NAME => 'Errors:URL'}`
- B. `create 'WebLogs', 'Errors' {NAME => 'IP', NAME => 'URL'}`
- C. `create 'WebLogs', 'Errors:IP', 'Errors:URL'`
- D. `create 'WebLogs', 'Errors'`

Correct Answer: C

QUESTION 4



You have a table with 5 TB of data, 10 RegionServers, and a region size of 256MB. You want to continue with puts to widely disbursed row ids in your table. Which of the following will improve write performance?

- A. Increase your buffer cache in the RegionServers
- B. Increase the number of RegionServers to 15
- C. Decrease your number of RegionServers to 5
- D. Decrease your region size to 128MB

Correct Answer: C

QUESTION 5

The cells in a given row have versions that range from 1000 to 2000. You execute a delete specifying the value 3000 for the version. What is the outcome?

- A. The delete fails with an error.
- B. Only cells equal to the Specified version are deleted.
- C. The entire row is deleted.
- D. Nothing in the row is deleted.

Correct Answer: C

Reference: <http://archive.cloudera.com/cdh4/cdh/4/hbase/book.html#delete> (scroll below and see 5.8.1.5. Delete topic, read the last paragraph)

[CCB-400 VCE Dumps](#)

[CCB-400 Practice Test](#)

[CCB-400 Study Guide](#)