VCE & PDF
GeekCert.com

E20-340^Q&As

Clariion solutiongs implementation

Pass EMC E20-340 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/e20-340.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

What is the purpose of the ArrayCommPath setting in a CLARiiON storage system?

A. It enables LUNZ if LUN0 is not assigned to a host.

B. It indicates the failover mode for the selected initiator - 0, 1, 2, 3, or 4.

C. It sets the parameters for the entire storage system on a per-host basis.

D. It is the CLARiiON module that supports ALUA functions.

Correct Answer: A

QUESTION 2

The Access Logix ACL entries consist of the LUN UID and which other two elements?

A. Host HBA WWN and CLARiiON SP port WWN

B. Host HBA WWPN and CLARiiON SP port WWPN

C. Host SID and CLARiiON serial number

D. Host HBA WWN and CLARiiON serial number

Correct Answer: A

QUESTION 3

A new customer has expressed interest in upgrading their FCIP infrastructure. Currently their regional office supports over 180 users. They would like to obtain storage media encryption capability and eventually add RecoverPoint.

Which solution would you recommend?

A. MDS-9506 with the multi-services switching module

B. MDS-9506 with the storage services module

C. MDS-9509 with the storage services node

D. MDS-9509 with an MDS 48-port FC module

Correct Answer: A

QUESTION 4

A new switch is received and needs to be connected into an existing SAN. What port type is used for the ISL trunking feature?

A. E_port

B. F_port

C. FL_port

D. G_port

Correct Answer: A

QUESTION 5

Which two scenarios can be implemented in iSCSI and FC SAN?

a.

Single server connected to both a CLARiiON FC and a CLARiiON iSCSI storage system.

b.

NIC and iSCSI HBA connections mixed in the same server.

c.

Servers with iSCSI HBAs and servers with NICs connected to the same iSCSI storage system.

d.

Servers with HBAs and servers with iSCSI HBAs connected to the same storage system.

A.

C and D

B.

A and C

C.

A and B

D.

B and D

Correct Answer: A