



# E20-377<sup>Q&As</sup>

RecoverPoint/SE Specialist Exam for Implementation Engineers

**Pass EMC E20-377 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/e20-377.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

What are the recommended applications to bind and unbind thin devices from a pool?

- A. Symmwin or Symmetrix Management Console
- B. Solutions Enabler or Symmetrix Management Console
- C. Solutions Enabler or Symmwin
- D. Windows Disk Manager or Symmwin

Correct Answer: B

### QUESTION 2

Refer to the exhibit

What is the correct state for the Standard and RI-BCV prior to issuing a symreplicate start command?





- A. Synchronized
- B. Suspended
- C. Split
- D. Write-Enable

Correct Answer: C

### QUESTION 3

When an unconfigured device has to be added to a V-Max, which locks are placed?

- A. Configuration and back-end
- B. Configuration and front-end device
- C. Director and back-end
- D. Front-end device and back-end device

Correct Answer: A

### QUESTION 4

Open Replicator will be used to move data from a Symmetrix V-Max array to a CLARiiON array. The CLARiiON has NOT been discovered by the host on which the Open Replicator commands are issued. Which information has to be specified in the Open Replicator device file?

- A. The CLARiiON Array ID and LUN ID
- B. The WWN of the CLARiiON LUN
- C. The CLARiiON Array ID and WWN of the CLARiiON LUN
- D. The WWN and LUN ID of the CLARiiON LUN

Correct Answer: B

### QUESTION 5



After acquiring a company 300 hundred miles from their current office the customer has asked EMC to help to design a single hop application recovery plan after careful analysis of the work load and available bandwidth, SRDF/AR was selected as the solution.

If the SRDF/AR cycle time is set to 90 minutes, what is the maximum potential data loss?

- A. 2 hours of data
- B. 1.5 hours of data
- C. 4.5 hours of data
- D. 3 hours of data

Correct Answer: A

[Latest E20-377 Dumps](#)

[E20-377 PDF Dumps](#)

[E20-377 Braindumps](#)