



# E20-598<sup>Q&As</sup>

Backup and Recovery - Avamar Specialist Exam for Storage Administrators

**Pass EMC E20-598 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/e20-598.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

By default, which percentage of the file system storage space is reserved for operating systems and checkpoint overhead on the EMC Avamar server?

- A. 10
- B. 20
- C. 35
- D. 65

Correct Answer: C






### QUESTION 2

In the EMC Avamar Administration Server View, what color is the status indicator when the node cannot communicate with the administrator server?

- A. Gray
- B. Red
- C. Blue
- D. Amber

Correct Answer: A

**Table 44** Server Monitor Avamar tab properties (page 1 of 2)

Property	Description
Node	
Status indicators	<p>One of the following:</p> <ul style="list-style-type: none"><li> Online (green)—The node is functioning properly.</li><li> Read-Only (blue)—This status occurs normally as background operations are performed and when backups have been suspended.</li><li> Time-Out (gray)—MCS could not communicate with this node.</li><li> Unknown (yellow)—Node status cannot be determined.</li><li> Offline (red)—The node has experienced a problem. If ConnectEMC has been enabled, a Service Request (SR) is logged. <sup>1</sup></li></ul>



### QUESTION 3

A Microsoft Windows user is about to initiate an on-demand backup from the client interface when the utility node fails on their multi-node EMC Avamar grid. What must be done prior to initiating the backup to ensure the backup will complete successfully?

- A. Nothing. Backups are performed from the client to the storage nodes directly.
- B. The utility node must be replaced and the configuration restored prior to starting the backup.
- C. The spare node must be converted to a utility node and the configuration restored to it prior to starting the backup.
- D. The client must be activated temporarily to the first storage node and then the backup can continue.

Correct Answer: A

---

### QUESTION 4

Which port does EMC Avamar use to access the Management Console database for reporting?

- A. 5555
- B. 7778
- C. 8443
- D. 8080

Correct Answer: A

---

### QUESTION 5

Where are replication log files stored on an EMC Avamar server?

- A. /usr/local/avamar/var/cron/replicate.log
- B. /usr/local/avamar/var/log/replicate.log
- C. /usr/local/avamar/var/cron/log/replicate.log
- D. /usr/local/avamar/log/replicate.log

Correct Answer: A

[E20-598 PDF Dumps](#)

[E20-598 VCE Dumps](#)

[E20-598 Practice Test](#)