



HH0-220^{Q&As}

HDS Certified Implmenter-Modular

Pass Hitachi HH0-220 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hh0-220.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the correct procedure to replace a suspected SAS interface cable connected to the last drive box (DBL) of a Hitachi Unified Storage system?

- A. Replace the suspected SAS interface cable by a new one.
- B. Using SNM2, disable the suspected SAS link, replace the cable and enable the SAS link.
- C. Using the WEB tool, disable the suspected SAS link, replace the cable and enable the SAS link.
- D. Slide out the I/O module from the DBL, replace the cable and slide the I/O module back in.

Correct Answer: D

QUESTION 2

You must install Hitachi Dynamic Link Manager (HDLM) on a customer's server but you are not sure if the server HBA types and versions are supported. Which two actions would help you find this information? (Choose two.)

- A. Check the HDLM release notes.
- B. Call the HDS Customer Support Center.
- C. Check the HDLM Concepts and Planning Guide.
- D. Access the HiFire Web site to verify the configuration.

Correct Answer: AD

QUESTION 3

Which two Hitachi Dynamic Link Manager documents provide detailed information of supported Fibre Channel HBA drivers? (Choose two.)

- A. Hitachi Engineering Change Notice (ECN)
- B. Hitachi Dynamic Link Manager Release Notes
- C. Hitachi Dynamic Link Manager Concepts and Planning Guide
- D. Hitachi Dynamic Link Manager for Operating Systems User's Guide

Correct Answer: AB

QUESTION 4

Which performance feature is provided by the Hitachi Unified Storage systems controller architecture?



- A. automatic cache segment resizing
- B. automatic controller load balancing
- C. automatic front-end storage group load balancing
- D. automatic front-end port hardware load balancing

Correct Answer: B

QUESTION 5

A storage administrator would like to connect 10 hosts into the same FC ports of a Hitachi Unified Storage system. They are concerned that one host with high I/Os will impact the other hosts on the same FC ports. Which HBA parameter should be set to limit the number of outstanding I/Os on each host?

- A. queue depth
- B. command length
- C. command depth
- D. queue length

Correct Answer: A

[HH0-220 Study Guide](#)

[HH0-220 Exam Questions](#)

[HH0-220 Braindumps](#)