



HH0-450^{Q&As}

Hitachi Data Systems Storage Architect-Hitachi NAS Platform

Pass Hitachi HH0-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hh0-450.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A customer is using the JetMirror object-based replication to mirror their data to a DR site. They now want to perform a controlled failover due to a planned power outage in their primary site without losing any data. Which two statements are correct? (Choose two.)

- A. The customer must perform a syslock on the primary FS before failover.
- B. The customer must have a scheduled replication window of one hour or less.
- C. The customer must promote the FS on the DR site.
- D. The customer must do a initial synchronization before failover.

Correct Answer: AC

QUESTION 2

A production Hitachi NAS Platform is connected to a Hitachi VSP with a storage pool consisting of SATA drives. To improve performance, the customer wants to migrate to SAS drives on an externalized Hitachi AMS2300 with minimal customer involvement and minimal impact to the system and users. Which two products should be deployed? (Choose two.)

- A. Hitachi Universal Replicator
- B. Hitachi Tiered Storage Manager
- C. Hitachi Device Manager
- D. Hitachi Tuning Manager

Correct Answer: BC

QUESTION 3

Your customer wants to issue administrative commands to a Hitachi NAS Platform over their data network using scripting. The clients on the data network have no routes defined to allow access on the management network. What must you do?

- A. Change the firewall setting in SMU to allow access to the admin EVS.
- B. Assign an IP address to the admin EVS on the data network aggregate.
- C. Run the scripted commands against any existing file services EVS.
- D. Add an additional IP address to the file services EVS used by the clients.

Correct Answer: B



QUESTION 4

What are two ways of controlling the anti-virus on Hitachi NAS Platform nodes? (Choose two.)

- A. Select the round robin algorithm on the multi-scan engine configuration screen.
- B. Set up the inclusion list.
- C. Enable anti-virus at the EVS level.
- D. Modify the virus background checking policies.

Correct Answer: BC

QUESTION 5

Which three statements describe the de-migration process of Data Migrator on a Hitachi NAS Platform? (Choose three.)

- A. The entire directory tree is migrated as a single instance.
- B. The use of wildcard characters is permitted.
- C. Reverse migration cannot be canceled once initiated.
- D. An event will be raised when a file has been reverse-migrated.
- E. Reverse migration is a background process.

Correct Answer: BDE

[Latest HH0-450 Dumps](#)

[HH0-450 PDF Dumps](#)

[HH0-450 VCE Dumps](#)