



# HP0-815<sup>Q&As</sup>

Advanced SAN Architecture

**Pass HP HP0-815 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hp0-815.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

What happens in the Storage Assessment phase of the SAN architecture approach? (Choose three.)

- A. selection and establishment of guidelines models, principles, and standards for the SAN
- B. description of the feasibility of an effective solution based on obstacles and constraints
- C. an inventory of systems, software, employee skills, and internal processes/documentation
- D. analysis and documentation of business requirements, organization, physical environment, networks, and infrastructure management
- E. Business data is classified, utilization of data is explored, ownership and usage statistics of application volumes on systems are reported.

Correct Answer: CDE

---

#### QUESTION 2

Backbone SANs are best suited for what type of traffic?

- A. many-to-many
- B. one-to-one
- C. many-to-one
- D. localized

Correct Answer: A

---

#### QUESTION 3

How long does it typically take to create a SAN architecture for an enterprise-class customer?

- A. days to weeks
- B. hours
- C. weeks to months
- D. months to years

Correct Answer: C

---

#### QUESTION 4

When I/O traffic patterns are unknown, what is the recommended SAN topology?



- A. ring
- B. backbone
- C. meshed
- D. cascaded

Correct Answer: B

---

#### QUESTION 5

A SAN administrator needs to change the Domain ID and Core PID parameters on a switch that is part of a production fabric. Which two statements about this update are true? (Choose two.)

- A. This process can be performed with the switch online without disruption.
- B. The Core PID parameter does not need to be manually changed; it will automatically be selected.
- C. The switch must be rebooted to set the Domain ID and Core PID.
- D. This process cannot be performed with the switch online and is disruptive.
- E. The Core PID parameter must be manually changed as it is set to a default value in the factory.

Correct Answer: DE

[HP0-815 VCE Dumps](#)

[HP0-815 Practice Test](#)

[HP0-815 Exam Questions](#)