



HP2-T26^{Q&As}

Servicing HP BladeSystem Solutions

Pass HP HP2-T26 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hp2-t26.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A customer has an SB40c paired with a full height blade. The blade cannot access the SB40c storage. Which component in the blade may need to be replaced?

- A. QLogic or Emulex HBA mezzanine card
- B. InfiniBand mezzanine card
- C. P700 Smart Array mezzanine card
- D. PCI Express Mezzanine Pass-Thru

Correct Answer: D

QUESTION 2

Which serial communication parameters must be set on the terminal emulator to connect the Onboard Administrator?

- A. 9600 E, 8, 1
- B. 19200 E, 7, 1
- C. 19200 N, 7, 1
- D. 9600 N, 8, 1

Correct Answer: D

QUESTION 3

Which HP BladeSystem component is used for power allocation and control for all blades and interconnects?

- A. Rack and Power Manager
- B. Power Manager
- C. Onboard Administrator
- D. Insight Display

Correct Answer: C

QUESTION 4

You are installing a new HP BladeSystem c7000 enclosure. The customer wants to configure the iLO and interconnect IPs so that they are automatically maintained during a hardware swap.

How should you configure the enclosure?



- A. Use the Insight Display fixed IP feature.
- B. Use Enclosure-Based IP Addressing.
- C. Use Insight Control Server Deployment to configure the enclosure.
- D. Configure the IP on each device and enable enclosure IP mode.

Correct Answer: B

QUESTION 5

Place the options steps in the correct order.

Select and Place:

Steps In Order

| | |
|---|-------------------|
| 1 | (place step here) |
| 2 | (place step here) |
| 3 | (place step here) |
| 4 | (place step here) |

| | | | |
|--|----------------------------|----------------------------------|--------------------------|
| Update the Virtual Connect Ethernet firmware | Update all server firmware | Update the Unboard Administrator | Reboot the server blades |
|--|----------------------------|----------------------------------|--------------------------|

Select and Place:

Steps In Order

| | |
|---|-------------------|
| 1 | (place step here) |
| 2 | (place step here) |
| 3 | (place step here) |
| 4 | (place step here) |

| | | | |
|--|----------------------------|----------------------------------|--------------------------|
| Update the Virtual Connect Ethernet firmware | Update all server firmware | Update the Unboard Administrator | Reboot the server blades |
|--|----------------------------|----------------------------------|--------------------------|

Correct Answer:



Steps In Order

- 1 Update the Urboard-Administrator
- 2 Update the Virtual Connect Ethernet firmware
- 3 Update all server firmware
- 4 Reboot the server blades

| | | | |
|--|--|--|--|
| | | | |
|--|--|--|--|

[HP2-T26 PDF Dumps](#)

[HP2-T26 VCE Dumps](#)

[HP2-T26 Study Guide](#)