



HP2-Z30^{Q&As}

Fast Track - Applying HP FlexNetwork Fundamentals

Pass HP HP2-Z30 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/hp2-z30.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which component of an HP Comware switch controls logging on to a syslog server?

- A. Log Parser
- B. Event Analyzer
- C. Information Center
- D. Event Log

Correct Answer: C

QUESTION 2

A network administrator has installed IMC and the appropriate licenses. The network administrator is attempting to import the HP Comware and HP ProVision switches into IMC but is experiencing problems importing the Comware switches. The network administrator verifies the SNMPv2c configuration on both sets of switches and the SNMP configuration in IMC. The SNMP parameters are correct.

What is the cause of the import problem?

- A. Comware switches implement SNMPv3 by default.
- B. Comware switches require SSH to be configured for remote CLI access.
- C. Comware switches are not fully supported by IMC.
- D. Comware switches do not have telnet fully configured.

Correct Answer: D

QUESTION 3

What are the correct factory default settings when the HP Comware and Provision switches are originally booted?

- A. Provision and Comware switches have Telnet enabled.
- B. Provision and Comware switches have all Layer 2 interfaces disabled.
- C. Provision and Comware switches have default passwords defined.
- D. Provision and Comware switches have Layer 3 switching disabled.

Correct Answer: D

QUESTION 4



A network administrator has set up a link between two HP ProVision switches. Both switches have an IP address in VLAN 1 and can ping each other in VLAN 1. The network administrator then creates VLAN 2 and tags it to same link of both switches.

How can the network administrator verify that connectivity in VLAN2 is functional between the two switches?

- A. Assign each switch an IP address in VLAN 2 and use LLDP to test connectivity.
- B. Use either LLDP or ARP to test connectivity
- C. Assign each switch an ip address in VLAN 2, and use ICMP or LLDP to test connectivity
- D. Assign each switch an IP address in VLAN 2, and use ICMP to test connectivity
- E. Use LLDP to test connectivity

Correct Answer: C

QUESTION 5

Which console cable is used on an HP Comware switch?

- A. cross-over
- B. rollover
- C. USB
- D. straight-through

Correct Answer: B

[Latest HP2-Z30 Dumps](#)

[HP2-Z30 VCE Dumps](#)

[HP2-Z30 Exam Questions](#)