



# JN0-321<sup>Q&As</sup>

DX, Associate(JNCIA-DX)

## Pass Juniper JN0-321 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-321.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





#### QUESTION 1

Router A and B are connected with a point to point OC3 interface. Each router's OC3 interface is configured for both Level 1 and Level 2. The routers are configured the same are a. How many ISIS adjacencies exist between the two routers?

- A. 0
- B. 1
- C. 2
- D. 3

Correct Answer: C

---

#### QUESTION 2

When configuring SMTP Health Check parameters for SLB, which two statements are true? (Choose two.)

- A. This parameter requires no configuration, it is enabled by default.
- B. SMTP health checking does not work with SMTPS, it only works with plain text SMTP servers.
- C. SMTP health checking works with any SMTP application.
- D. The DX appliance establishes a TCP connection for handshaking with the server.

Correct Answer: BD

---

#### QUESTION 3

Which two authentication protocols can be configured for RIP on an ERX Edge Router?

- A. PAP
- B. MD5
- C. CHAP
- D. Clear text

Correct Answer: BD

---

#### QUESTION 4

There are three routers on a Gigabit Ethernet LAN: Router A, Router B, and Router C, Router A is the Designated intermediate System (DIS) at Level 1 for that LAN. Router A's DIS priority is 64. The LAN is a Level 1 only link. Router D has just been powered up on that same LAN and its DIS priority is 80.



Which statement is true?

- A. Router A remains the DIS and generates a new pseudonode LSP for that LAN.
- B. Router A remains the DIS and NO new pseudonode LSP is generated for that LAN.
- C. Router D becomes the new DIS, generates a new pseudonode LSP for that LAN, And purges the oldpseudnode LSP generated by Router A.
- D. Router D becomes the new DIS, does NOT generate a new pseudnode LSP for That LAN, and doesNOT purge the old psednode LSP generated by Router A.

Correct Answer: C

---

#### QUESTION 5

BGP route dampening is configured on a BGP router. Whose routing behavior is affected by this configuration?

- A. upstream EBGP neighbors
- B. downstream EBGP neighbors
- C. upstream IBGP neighbors learned by IBGP peers
- D. downstream IBGP neiphors learned by IBGP peers

Correct Answer: A

[Latest JN0-321 Dumps](#)

[JN0-321 Practice Test](#)

[JN0-321 Exam Questions](#)