



JN0-321^{Q&As}

DX, Associate(JNCIA-DX)

Pass Juniper JN0-321 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-321.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which configuration command sets the MPLS interface bandwidth to 15 Mbps?

- A. set bandwidth 15
- B. mpls bandwidth 15
- C. set bandwidth 15000
- D. mpls bandwidth 15000

Correct Answer: D

QUESTION 2

Which command displays the result of a loopback test you executed on a CT3 line module in slot 5, port 0,t1 number 4?

- A. show interface 5/0:4
- B. show interface 5/0:4/1
- C. show controllers t3 5/0:4
- D. show controllers t3 5/0:4/1

Correct Answer: C

QUESTION 3

An enterprise has three servers behind a Juniper DX SLB, labeled Server A, Server Band Server C. They have chosen to use the Weighted Round Robin algorithm. Server A has been assigned a weight of 10,Server B a weight of 10, and Server C a weight of 0.

What percent of traffic will go to Server C?

- A. 0%
- B. 10%
- C. 100%
- D. 33%

Correct Answer: A

QUESTION 4



An enterprise uses a Webtiered application that provides NTLM end user authentication. What is the required Cluster option?

- A. DSR
- B. Connect Method
- C. Connection Binding
- D. Sticky Load Balancing

Correct Answer: C

QUESTION 5

When running SSL on a nonweb application, where are the secure connections made?

- A. between the client and the DX appliance and between the DX appliance and the target servers
- B. directly between the client and the target server(s)
- C. between the client and the DX appliance
- D. between the DX appliance and the target server(s)

Correct Answer: C

[JN0-321 PDF Dumps](#)

[JN0-321 VCE Dumps](#)

[JN0-321 Study Guide](#)