



JN0-332^{Q&As}

Juniper Networks Certified Internet Specialist, SEC (JNCIS-SEC)

Pass Juniper JN0-332 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-332.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which three components can be leveraged when defining a local whitelist or blacklist for antispam on a branch SRX Series device? (Choose three.)

- A. spam assassin filtering score
- B. sender country
- C. sender IP address
- D. sender domain
- E. sender e-mail address

Correct Answer: CDE

QUESTION 2

Which feature on the SRX Series device would be processed first for transit traffic?

- A. Zone
- B. NAT
- C. Screens
- D. Security policies

Correct Answer: C

QUESTION 3

Which two statements are true about AH? (Choose two.)

- A. AH provides data integrity.
- B. AH is identified by IP protocol 50.
- C. AH is identified by IP protocol 51.
- D. AH cannot work in conjunction with ESP

Correct Answer: AC

QUESTION 4

Click the Exhibit button.



```
{primary:node0}
user@host> show security flow session
node0:
-----
Session ID: 19, Policy name: self-traffic-policy/1, State: Backup, Timeout:
1752, Valid
  In: 6.6.6.2/500 --> 1.1.1.2/500;udp, If: ge-0/0/3.0, Pkts: 0, Bytes: 0
  Out: 1.1.1.2/500 --> 6.6.6.2/500;udp, If: .local..0, Pkts: 0, Bytes: 0
```

Which two statements are true about the output shown in the exhibit? (Choose two)

- A. The IKE protocol has been enabled as a system service for host inbound traffic.
- B. The session displayed represents traffic transiting an IPsec tunnel.
- C. The session displayed represents IPsec control traffic.
- D. A user has configured the self-traffic-policy to allow IKE traffic.

Correct Answer: AC

QUESTION 5

You are asked to implement a chassis cluster on high-end SRX Series devices. What are two requirements? (Choose two.)

- A. There can be up to two redundancy groups per chassis cluster.
- B. The chassis models must be the same.
- C. The data plane can use SPC ports.
- D. SPCs must be placed in identical slots in all chassis.

Correct Answer: BD

[JN0-332 PDF Dumps](#)

[JN0-332 Exam Questions](#)

[JN0-332 Braindumps](#)