



JN0-633^{Q&As}

Security, Professional (JNCIP-SEC)

Pass Juniper JN0-633 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/jn0-633.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

You want to implement an IPsec VPN on an SRX device using PKI certificates for authentication. As part of the implementation, you are required to ensure that the certificate submission, renewal, and retrieval processes are handled automatically from the certificate authority. Regarding this scenario, which statement is correct?

- A. You can use SCEP to accomplish this behavior.
- B. You can use OCSP to accomplish this behavior.
- C. You can use CRL to accomplish this behavior.
- D. You can use SPKI to accomplish this behavior.

Correct Answer: A

QUESTION 2

You have installed a new IPS license on your SRX device and successfully downloaded the attack signature database. However, when you run the command to install the database, the database fails to install. What are two reasons for the failure? (Choose two.)

- A. The file system on the SRX device has insufficient free space to install the database.
- B. The downloaded signature database is corrupt.
- C. The previous version of the database must be uninstalled first.
- D. The SRX device does not have the high memory option installed.

Correct Answer: AB

QUESTION 3

You are attempting to establish an IPsec VPN between two SRX devices. However, there is another device between the SRX devices that does not pass traffic that is using UDP port 4500.

How would you resolve this problem?

- A. Enable NAT-T.
- B. Disable NAT-T.
- C. Disable PAT.
- D. Enable PAT.

Correct Answer: B



QUESTION 4

In which situation is NAT proxy NDP required?

- A. when translated addresses belong to the same subnet as the ingress interface
- B. when filter-based forwarding and static NAT are used on the same interface
- C. when working with static NAT scenarios
- D. when the security device operates in transparent mode

Correct Answer: C

QUESTION 5

You have just created a few hundred application firewall rules on an SRX device and applied them to the appropriate firewall policies. However, you are concerned that the SRX device might become overwhelmed with the increased processing required to process traffic through the application firewall rules.

Which three actions will help reduce the amount of processing required by the application firewall rules? (Choose three.)

- A. Use stateless firewall filtering to block the unwanted traffic.
- B. Implement AppQoS to drop the unwanted traffic.
- C. Implement screen options to block the unwanted traffic.
- D. Implement IPS to drop the unwanted traffic.
- E. Use security policies to block the unwanted traffic.

Correct Answer: ACE

[Latest JN0-633 Dumps](#)

[JN0-633 Study Guide](#)

[JN0-633 Exam Questions](#)