

JN0-660^{Q&As}

Service Provider Routing and Switching, Professional

Pass Juniper JN0-660 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.geekcert.com/jn0-660.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Click the Exhibit button.

```
user@router> show route table inet.0 protocol ospf
inet.0: 17 destinations, 17 routes (17 active, 0 holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both
224.0.0.5/32
                  *[OSPF/10] 1w2d 21:43:55, metric 1
                     MultiRecv
user@router> show ospf database
   OSPF database, Area 0.0.0.0
 Type
           ID
                           Adv Rtr
                                              Seq
                                                      Age Opt Cksum Len
        67.176.255.1
                       67.176.255.1
Router
                                         0x8000001/6 1138 0x22 0x3f8e 48
        67.176.255.2
                         67.176.255.2
                                        0x80000151 1131 0x22 0xa349
Router
Router *67.176.255.3
                                         0x80000152 1137
                        67.176.255.3
                                                           0x22 0xa733
       67.176.255.4
                        67.176.255.4
                                          0x80000167 1138 0x22 0x9937
Router
Network 67.176.10.2
                         67.176.255.1
                                         0x80000007 1138 0x22 0x7ae2
   OSPF AS SCOPE link state database
 Type
           ID
                           Adv Rtr
                                              Seq
                                                      Age Opt Cksum Len
Extern
        10.128.0.0
                         67.176.255.2
                                          0x8000013a 2118
                                                           0x22 0xda22
Extern
        10.128.55.32
                         67.176.255.2
                                          0x8000013a 1624
                                                           0x22 0xe1f
        10.128.128.0
                         67.176.255.2
                                          0x8000013a
                                                      628
                                                           0x22 0xd5a6 36
Extern
        10.128.128.32
                        67.176.255.2
                                         0x8000013a 127 0x22 0xe7fb 36
Extern
user@router> show ospf neighbor
                Interface
                                       State
                                                ID
                                                                 Pri Dead
                                                67.176.255.4
67.176.10.5
                ge-0/0/8.0
                                      Full
                                                                 128
67.176.10.2
                ge-0/0/8.0
                                       Full1
                                                67.176.255.1
                                                                 128
                                                                        39
67.176.10.3
                ge-0/0/8.0
                                       ExStart 67.176.255.2
                                                                   1
                                                                        36
user@router> show ospf interface ge-0/0/8.0 extensive
                                                          BDR ID
Interface
                   State
                          Area
                                          DR ID
                                                                          Mors
                   PtToPt 0.0.0.0
ge-0/0/8.0
                                           0.0.0.0
                                                          0.0.0.0
                                                                             3
  Type: P2MP, Address: 67.176.10.4, Mask: 255.255.255.0, MTU: 1500, Cost: 1
  Adj count: 2
  Hello: 10, Dead: 40, ReXmit: 5, Not Stub
  Auth type: None
  Protection type: None
  Topology default (ID 0) -> Cost: 1
```

Based on the exhibit, why is the router not installing routes in the OSPF database into the routing table?

- A. The neighbor is stuck in the ExStart state
- B. The routes are going to a different table than inet.0
- C. There is an interface type mismatch
- D. There is an MTU mismatch

Correct Answer: C

https://www.geekcert.com/jn0-660.html

QUESTION 2


Which two statements regarding OSPFv2 or OSPFv3 authentication are correct? (Choose two.)

- A. OSPFv2 supports MD5 authentication.
- B. OSPFv2 supports MD5 or SHA authentication.
- C. OSPFv2 relies on the native security stack that uses IPsec.
- D. OSPFv3 relies on the native security stack that uses IPsec.

Correct Answer: D

QUESTION 3

Click the Exhibit button.



Referring to the exhibit, which statement is true assuming BGP Layer 2 VPN signaling?

- A. PE1 receives two BGP NLRI updates, each containing a remote site ID, a label base, and Layer 2 encapsulation.
- B. PE2 receives one BGP NLRI update containing a remote site ID, a label base, and Layer 2 encapsulation.
- C. PE2 receives two BGP NLRI updates, each containing a remote site ID, label vc, and Layer 2 encapsulation.
- D. PE1 receives one BGP NLRI for VPN A containing only a remote site ID and a label offset value.

Correct Answer: A

QUESTION 4

In which two ways does VPLS populate the MAC table? (Choose two.)



https://www.geekcert.com/jn0-660.html

2024 Latest geekcert JN0-660 PDF and VCE dumps Download

- A. dynamically using BGP
- B. dynamically using the source MAC address on received frames
- C. dynamically using LDP
- D. statically using CLI

Correct Answer: BD

QUESTION 5

Click the Exhibit button.

```
routing-options {
    interface-routes {
        rib-group inet ifrg;
    rib-groups {
        ifrq {
             import-rib [ inet.0 inet.2 ];
        merg {
             export-rib inet.2;
             import-rib inet.2;
protocols {
    msdp {
        rib-group mcrg;
        group lab {
             peer 192.168.6.18 {
                 local-address 192.168.6.17;
    1
    pim {
        dense-groups {
            224.0.1.39/32;
            224.0.1.40/02;
        rib-group inet mcrg;
        rp {
            local {
                 address 192.168.1.1;
        interface all {
            mode sparse-dense;
            version 1;
        )
    }
}
```

What is the significance of RIB groups, as shown in the exhibit?

- A. RIB groups alter the multicast RPF check table to inet.0.
- B. RIB groups alter the multicast RPF check table to inet.2.
- C. RIB groups alter the multicast RPF check table to inet.4.
- D. RIB groups alter the multicast RPF check table to inet.3.



https://www.geekcert.com/jn0-660.html 2024 Latest geekcert JN0-660 PDF and VCE dumps Download

Correct Answer: B

Latest JN0-660 Dumps

JN0-660 VCE Dumps

JN0-660 Study Guide