



NS0-504^{Q&As}

NetApp Certified Implementation Engineer - SAN, Cluster-Mode

Pass NetApp NS0-504 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ns0-504.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

The storage administrator wants to ensure resilient non-interruptive access to a LUN in a cluster even if the volume containing the LUN is moved to any node within the cluster. What is the minimum recommended method to accomplish this requirement?

- A. Create a single fabric design with a single LIF on each node.
- B. Create a single fabric design with two LIFs on each node.
- C. Create a dual fabric design with a single LIF to one of the fabrics on each node.
- D. Create a dual fabric design with a single LIF to each of the fabrics on each node.

Correct Answer: A

QUESTION 2

Which four FC fabric topologies does NetApp support? (Choose four.)

- A. four FC switches with multiple Inter-Switch Links (ISLs) between each pair of switches
- B. ten FC switches per fabric, daisy chained with a single ISL between switches
- C. four FC switches with multiple ISLs between ALL switches
- D. eight FC switches with no more than a single ISL between switches in a cascade topology
- E. dual FC switches with no ISLs
- F. a single FC switch
- G. a switched fabric that has 65537 ports

Correct Answer: ACEF

QUESTION 3

Which two statements are true in a SnapMirror LS mirror relationship? (Choose two.)

- A. Client requests to write data are allowed if the user is root.
- B. Client requests to write data are denied unless accessing the admin share.
- C. Client requests to read data are only allowed if the mirror is up-to-date.
- D. Client requests to read data are redirected to the LS mirror destination volumes.

Correct Answer: BD



QUESTION 4

Which MetroCluster configuration procedure is recommended for re-establishing a mirrored volume that was in a level-0 resynchronization state when it failed?

- A. Determine which volumes are at the remote and disaster sites.
- B. Re-create the synchronous mirror.
- C. Rejoin the two volumes.
- D. Turn on power to the cluster node at the disaster site.

Correct Answer: B

QUESTION 5

Which topology allows for guaranteed maximum network performance for iSCSI?

- A. isolated VLAN network
- B. MetroWAN network
- C. direct connect
- D. WAN network

Correct Answer: C

[NS0-504 VCE Dumps](#)

[NS0-504 Practice Test](#)

[NS0-504 Exam Questions](#)