



PW0-105^{Q&As}

Certified Wireless Network Administrator (CWNA)

Pass EC-COUNCIL PW0-105 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/pw0-105.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EC-COUNCIL Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What term correctly completes the following sentence?

In an IEEE 802.11 frame, the IP packet is considered by the MAC layer to be a(n) _____.

- A. MAC Service Data Unit (MSDU)
- B. MAC Protocol Data Unit (MPDU)
- C. Bridge Protocol Data Unit (BPDU)
- D. PLCP Service Data Unit (PSDU)
- E. PLCP Protocol Data Unit (PPDU)

Correct Answer: A

QUESTION 2

Given: XYZ Company has decided to install an 802.11 WLAN system that will support 1000 wireless users, but they are concerned about network security. XYZ is interested in deploying standardized security features. In addition to WPA2-Enterprise with PEAP and role-based access control, XYZ would like to support management frame protection as well as a fast secure roaming protocol for future mobile handsets.

As XYZ Company selects a product to deploy, what two IEEE amendments should be supported to provide the management frame protection and fast secure roaming security features? (Choose two)

- A. 802.11j
- B. 802.11p
- C. 802.11r
- D. 802.11u
- E. 802.11w
- F. 802.11z

Correct Answer: CE

QUESTION 3

Given: As defined in the 802.11 specification, legacy Power Save requires an inefficient back-and-forth frame exchange process. Due to this inefficiency, many WLAN device implementations use a variation of

802.11 Power Save to accomplish the same function.

What non-standard power save behavior is used by most Wi-Fi devices in actual implementations?



- A. Client devices ignore the TIM field and automatically send PS-Poll frames after every beacon.
- B. After each beacon, the AP attempts to empty its frame buffer by sending Wake-on-WLAN frames to wake each dozing client.
- C. Request-to-Send and Clear-to-Send frame exchanges are used to trigger the delivery of buffered data.
- D. The Beacon interval is changed from the default 100 time units to 10 or less time units.
- E. Clients send null data frames to the AP and switch the power management bit from 1 to 0 to receive queued data.
- F. Stations send a CTS-to-self frame to the AP with a very long duration period so they can receive all of their buffered data at once.

Correct Answer: E

QUESTION 4

Why is it recommended for a wireless network administrator to disable 1 Mbps and 2 Mbps data rates on the WLAN infrastructure? (Choose two)

- A. To improve capacity in the BSS
- B. To reduce the size of the AP's effective service area
- C. To prevent 802.11b devices from associating
- D. To maximize the range of the highest data rates
- E. To prevent VoWiFi multicast frames
- F. To enable support for long preambles

Correct Answer: AB

QUESTION 5

What features were introduced in the IEEE 802.11h amendment in order to uphold regulatory requirements for 5 GHz operation? (Choose two)

- A. Automated Radio Measurement (ARM)
- B. Distributed Coordination Function (DCF)
- C. Frequency Shift Keying (FSK)
- D. Transmit Power Control (TPC)
- E. Radio Resource Management (RRM)
- F. Dynamic Frequency Selection (DFS)

Correct Answer: DF



VCE & PDF

GeekCert.com

<https://www.geekcert.com/pw0-105.html>

2024 Latest geekcert PW0-105 PDF and VCE dumps Download

[PW0-105 PDF Dumps](#)

[PW0-105 VCE Dumps](#)

[PW0-105 Exam Questions](#)