



# ACE-A1.2<sup>Q&As</sup>

Arista Certified Engineering Associate

## Pass Arista ACE-A1.2 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ace-a1-2.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Arista  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

How many line card slots are reserved for supervisors on the Arista 7300 series chassis switches?

- A. 1
- B. 2
- C. 4
- D. none

Correct Answer: B

Reference: [https://www.arista.com/assets/data/pdf/Datasheets/7300X\\_DS.pdf](https://www.arista.com/assets/data/pdf/Datasheets/7300X_DS.pdf) (page 4)

---

### QUESTION 2

When you fullrecover a switch from Aboot and a USB drive is present in the USB port of the switch, which of the following statements is true?

- A. Everything on the USB drive is deleted.
- B. Only Arista-sourced files are copied from the USB drive to flash: and the switch reboots.
- C. If the USB drive contains a fullrecover file and a boot-config file with a timestamp different than the one on USB flash drive, then the USB Drive's contents will be copied to flash, after which the switch will reboot.
- D. Nothing. The USB port is disabled when Aboot is active.

Correct Answer: C

Reference: <https://eos.arista.com/password-recovery-return-to-factory-default/> (how to prepare the USB drive)

---

### QUESTION 3

What is the command to set the switch to use EOS 4.15.1F.swi the next time it reloads?

- A. boot system flash:EOS-4.15.1.swi
- B. boot system 4.15.1F.swi
- C. boot system flash:/EOS-4.15.1F.swi
- D. boot system flash EOS-4.15.1F.swi

Correct Answer: C

---

### QUESTION 4



Which of the following Arista switch series support reversible airflow?

- A. 7150
- B. 7250QX
- C. 7010
- D. 7300

Correct Answer: D

Reference: <https://www.arista.com/en/products/7300-series>

### QUESTION 5

Given the following output, on what interface would you expect to see mirrored traffic when using tcpdump?

```
Arista#show monitor session Lab

Session Lab
-----
Source Ports:
  Both:      Et1
Destination Ports:
  Cpu:      active (mirror0)
```

- A. Ethernet1
- B. Et1
- C. cpu0
- D. mirror0

Correct Answer: B

Reference: [https://eos.arista.com/introduction-to-managing-eos-devices-troubleshooting/#362\\_Running\\_TCPDump\\_for\\_data-plane\\_traffic\\_natively\\_in\\_EOS](https://eos.arista.com/introduction-to-managing-eos-devices-troubleshooting/#362_Running_TCPDump_for_data-plane_traffic_natively_in_EOS)

[Latest ACE-A1.2 Dumps](#)

[ACE-A1.2 Study Guide](#)

[ACE-A1.2 Exam Questions](#)