



AD0-E103^{Q&As}

Adobe Experience Manager Developer

Pass Adobe AD0-E103 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ad0-e103.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Adobe
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A developer creates a template-type for building editable templates.

The resulting editable templates and pages must always contain a specific layout container that can NOT be deleted by the author.

How should the developer meet this requirement?

- A. Add the layout container component by including it on the actual page component.
- B. Add a content policy to the template-type to disable the removal of the layout container.
- C. Add the layout container component to the initial section of the template-type.
- D. Add the layout container component to the structure section of the template-type.

Correct Answer: B

QUESTION 2

A developer needs to create a banner component. This component shows an image across the full width of the page. A title is shown on top of the image. This text can be aligned to the left, middle, or right. The core components feature a teaser component which matches almost all requirements, but not all.

What is the most maintainable way for the developer to implement these requirements?

- A. Use and configure the teaser core component.
- B. Create a new custom component from scratch.
- C. Overlay the teaser core component.
- D. Inherit from the teaser core component.

Correct Answer: A

Reference: <https://helpx.adobe.com/es/experience-manager/kt/sites/using/getting-started-wknd-tutorialdevelop/part7.html>

QUESTION 3

A developer determines that the dispatcher is NOT refreshing the cached page `/content/sampleproject/sample.html` after it is updated.

The dispatcher.any contains the following entries:



```
/cache
{
  /docroot "/opt/dispatcher/cache"
  /statfile "/tmp/dispatcher-website.stat"
  /statfileslevel "2"

  /rules
  {
    /0000 {/glob "*" /type "allow"}
  }

  /invalidate
  {
    /0000 {/glob "*" /type "deny"}
  }
}
```

Refer to the \$DOCROOT directory below:

```
[user@group /opt/dispatcher/cache]$ ls -la
total 2
drwxr-xr-x. 5 apache apache 4096 Feb 11 11:41 .
drwxr-xr-x. 3 apache apache 4096 Nov 29 16:07 ..
drw-r--r--. 4 root root 4096 Feb 7 03:21 content
-rw-r--r--. 1 apache apache 0 Feb 7 03:19 .stat
```

The dispatcher needs to cache the page and refresh it after it gets updated. What action should the developer take to meet these requirements?

- A. Remove /statfile or /statfileslevel.
- B. Delete the contents of the DOCROOT directory.
- C. Change the value of the entry /statfileslevel to "3".
- D. Add the entry /0001 { /glob "-.html" /type "allow" } in the /invalidate section.

Correct Answer: D

**QUESTION 4**

A developer needs to change the label "Sites" in the navigation of AEM author to "Websites".

Which action should the developer take to achieve this?

- A. Modify the node `/libs/cq/core/content/nav/sites` by updating the `icr:title` property value.
- B. Change the code of `/libs/granite/ui/components/shell/clientlibs/shell/js/globalnav.js` to display the new value.
- C. Create a new node `/apps/cq/core/content/nav/sites` and update the property `icr:title`.
- D. Modify the code of `/libs/granite/ui/components/shell/globalnav/overlay/overlay.jsp` to display the new value.

Correct Answer: A

QUESTION 5

A developer is creating a custom method. This method must return a String property `y` from child `x`. the method must use only Sling APIs.

How should the developer retrieve property `y` of node `x`, and node `x` may or may NOT exist?



- A.

```
String y = ((ValueMap<String, String>) resource.getChild("x").getValueMap()).get("y", "");
```
- B.

```
String y = null;
Resource x = resource.getChild("x");
if (null!=x) {
    ValueMap<String> map = x.getValueMap();
    if (null!=map) {
        y = map.get("y", "");
    }
}
```
- C.

```
String y = null;
Node x = node.getNode("x");
if (null!=x) {
    Properties<Strings, String> properties = x.getProperties();
    if (null!=properties) {
        y = properties.get("y", "");
    }
}
```
- D.

```
String y = null;
Node x = node.getNode("x");
if (null!=x) {
    ValueMap<Strings, String> map = x.getValueMap();
    if (null!=map) {
        y = map.get("y", "");
    }
}
```

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: A