



BL0-100^{Q&As}

Nokia Bell Labs End-to-End 5G Foundation

Pass Nokia BL0-100 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/bl0-100.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which of the following is not a benefit of Network Slicing?

- A. Priority between different flows
- B. Privacy and segmentation between flows
- C. Recovery of network flows when they fail
- D. Differentiated QoS flows, for different services

Correct Answer: C

QUESTION 2

Which of the following defines a vertical Network Slice?

- A. When it serves a given customer for a specific purpose, such as a national energy network.
- B. When it cross all the network layers from the radio up to the core.
- C. When it serves a given common purpose, for a use case with a defined QoS (eg a use case in transportation, in energy).
- D. When it operates on the same layer of the ISO/OSI model.

Correct Answer: A

Reference: https://www.gsma.com/futurenetworks/wp-content/uploads/2018/06/Network-Slicing-UseCase-Requirements-_FInal-.pdf

QUESTION 3

Which of the following drive 5G low latency? (Choose two.)

- A. Support of up to 1 billion of IoT and sensors devices per km²
- B. Lower Time Transmission Interval (TTI)
- C. Higher spectral efficiency
- D. Edge Clouds

Correct Answer: BC

QUESTION 4

Which of the following best defines what is meant by Network Slice isolation?



- A. Security + Cloud isolation
- B. Resource + Security isolation
- C. Transport + Cloud isolation
- D. Resource + Traffic isolation

Correct Answer: B

Reference: https://www.gsma.com/futurenetworks/wp-content/uploads/2018/06/Network-Slicing-UseCase-Requirements_-_Final-.pdf

QUESTION 5

What is the purpose of the secondary authentication feature?

- A. To improve authentication between the User Equipment and the 5G Core.
- B. To improve authentication when connecting to different network slices.
- C. To authenticate the User Equipment coming from an untrusted non-3GPP access (N3IWF).
- D. To authenticate the User Equipment with an external data network.

Correct Answer: A

[Latest BL0-100 Dumps](#)

[BL0-100 Study Guide](#)

[BL0-100 Exam Questions](#)