



C2150-609^{Q&As}

IBM Security Access Manager V9.0 Deployment

Pass IBM C2150-609 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/c2150-609.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A deployment professional has a requirement to configure an OpenID Connect federation which does not allow the Relying Party to access the token endpoint.

Which grant type must be enabled when creating the federation?

- A. Implicit
- B. Refresh Token
- C. Client Credentials
- D. Authorization code

Correct Answer: D

Reference: <https://www.ibm.com/developerworks/library/se-configure-ISAM-reverse-proxy-PeP-to-OpenIDconnect-provider-trs/index.html>

QUESTION 2

Which action must be completed for an external high volume runtime database after upgrading a Security Access Manager appliance?

- A. Drop the runtime database
- B. Restart the external database
- C. Recreate the configuration table
- D. Run the Access Control update.sql files

Correct Answer: B

QUESTION 3

A customer has an IBM Security Access Manager V9.0 appliance cluster spanning two data centers A and

B. Data center A has the Primary Master and two Restricted nodes. Data center B has a Secondary Master and two Restricted Nodes.

A Load Balancer with redundancy across data centers provides sticky load balancing to reverse proxies in both data centers.

What is true if a disaster recovery testing scenario takes down all appliances in data center A?

- A. The Secondary Master will automatically be promoted to Primary Master



- B. Reverse Proxies in Data Center B will service all end-users with no intervention
- C. The Secondary Master has to be promoted to Primary for Data Center B to service end-users
- D. Reverse Proxies in Data Center B need to be recycled sequentially to handle users assigned Data Center A reverse proxies.

Correct Answer: A

QUESTION 4

A customer received a replacement hardware appliance, but on boot up it has a different firmware than that for IBM Security Access Manager (ISAM) V9.0. The appliance needs to be flashed to ISAM V9.0. The appliance needs to be rebooted with a bootable USB drive formatted as FAT32.

Which file format is needed to create the bootable drive?

- A. .iso
- B. .ova
- C. .pkg
- D. .img

Correct Answer: A

QUESTION 5

A deployment professional needs to update the certificate used by the LMI.

Which steps should the deployment professional follow to complete this task?

- A. Navigate in the LMI to manage system settings -> Management SSL Certificate -> Upload p12 file
- B. Navigate in the LMI to manage system settings -> Management SSL Certificate -> Request New Certificate from CA
- C. Navigate in the LMI to manage system settings -> Management SSL Certificate -> Update rt_profile_keys key file
- D. Navigate in the LMI to manage system settings -> Management Authorization -> Update rt_profile_keys key file

Correct Answer: B

[Latest C2150-609 Dumps](#)

[C2150-609 PDF Dumps](#)

[C2150-609 Practice Test](#)