

C4040-252^{Q&As}

Power Systems with POWER8 Enterprise Technical Sales Skills V1

Pass IBM C4040-252 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/C4040-252.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

800,000+ Satisfied Customers





QUESTION 1

Which hardware can be moved from a 770 to an E870 when doing a migration?

- A. PCIe 5802/5877 I/O drawer
- B. EXP24S SFF Gen2-bay drawer
- C. Memory DIMMs
- D. EXP30SSD I/O drawer

Correct Answer: B

QUESTION 2

Which of the following is a design consideration for the E870 / E880?

- A. The integrated SAS controllers in the system nodes manage all six SAS bays in the system node.
- B. A DVD drive must be included in either the system control unit or in a system node.
- C. Only low profile PCIe adapters are supported in the system node.
- D. Each system node has eight PCI Gen3 slots which are a mix of x8 and x16 PCIe slots.

Correct Answer: A

QUESTION 3

A client needs assistance with managing virtual machines and energy monitoring. The client is considering implementing Systems Director.

At a minimum, which edition of Systems Director would be needed?

- A. Basic
- B. Express
- C. Standard
- D. Enterprise

Correct Answer: C

QUESTION 4

A customer is purchasing a new POWER8 Server and will make a choice between PowerVM and PowerKVM.



What is an advantage of PowerVM over PowerKVM?

- A. NPIV support
- B. M R-IOV support
- C. Memory Deduplication
- D. Micro Threading
- Correct Answer: C

QUESTION 5

A customer would like to add a second HMC to an environment which consists of multiple POWER7 and POWER8 systems.

Which of the following is a requirement for both HMCs to be able to manage all the systems?

- A. All the POWER7 systems must be at the same firmware level.
- B. Both HMCs must be on the same HMC VLAN.
- C. Each HMC must be on a dedicated HMC VLAN.
- D. Both HMCs must be at the same code level.

Correct Answer: C

Latest C4040-252 Dumps

C4040-252 VCE Dumps

C4040-252 Practice Test



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.geekcert.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:



One Year Free Update



Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.



To ensure that you are spending on quality products, we provide 100% money back guarantee for 3<u>0 days</u>

Money Back Guarantee

from the date of purchase



Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.

Any charges made through this site will appear as Global Simulators Limited. All trademarks are the property of their respective owners. Copyright © geekcert, All Rights Reserved.