



# C9010-030<sup>Q&As</sup>

IBM i Administration V1

**Pass IBM C9010-030 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/c9010-030.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Two HMCs manage the same server. An administrator recently upgraded the HMC firmware from level V8 R8.2.0 to V8 R8.3.0 on one of the consoles. Shortly after, a connection error "Version Mismatch..." appeared on the second console.

Which process will resume the functionality for the second console?

- A. Reboot the second HMC.
- B. Upgrade the second HMC to V8 R8.3.0, re-initialize the server connection, and restore the partition profiles
- C. Select Reset or Remove Connections on the second HMC to reset the connection
- D. Install the latest service pack on the second HMC and re-initialize the server connection.

Correct Answer: C

---

### QUESTION 2

Several printers were moved from one IP subnet to another overnight. The printers are accessed by their Fully Qualified Domain Name (FQDN). The FQDNs were changed to resolve to the new addresses the following morning, but the IBM i will still not print to the new printers. The printers can be pinged by their IP addresses.

What is the cause of this problem?

- A. The DNS server was not restarted to present the new addresses.
- B. The network route to the new subnet is missing.
- C. IBM i has cached the resolved IP address before the change.
- D. CHGDEVPRT was not run on each device to get the new address

Correct Answer: C

---

### QUESTION 3

The HMC is backed up in two different ways for different purposes. Which identifies the correct tasks and usage?

- A. 1) Backup Critical System data is used prior to a firmware update 2) Save Upgrade Data is used for crash recovery purposes
- B. 1) Create Recoverable Image is used for crash recovery purposes 2) Save Upgrade Data is used prior to a firmware update
- C. 1) Save Upgrade Data is used prior to a firmware update 2) Back Up Management Console Data is used for crash recovery purposes



D. 1) Back Up Profile Data is used prior to a firmware update 2) Create Recoverable Image is used for crash recovery purposes

Correct Answer: D

---

#### QUESTION 4

A POWER8 system with a single FSP is running firmware SV830\_048. When the administrator goes to Fix Central, the latest firmware is SV830\_068\_050.

What is the effect of installing this software?

- A. The upgrade is disruptive because the only PowerKVM upgrades are concurrent when using OPAL.
- B. Since both the installed and the new firmware are at SV830, the upgrade will be concurrent when done from the OS.
- C. The upgrade is concurrent because the 068 and the 050 are not the same number.
- D. The upgrade would be disruptive as the 050 in the latest firmware is higher than the 048 currently running on the FSP.

Correct Answer: A

---

#### QUESTION 5

An additional DNS server has been configured on the local network. Given the following menu: 1 Work with TCP/IP interfaces 2 Work with TCP/IP routes

3.

Change TCP/IP attributes

4.

Work with TCP/IP port restrictions

5.

Work with TCP/IP remote system information

10.

Work with TCP/IP host table entnes

11.

Merge TCP/IP host table

12.

Change TCP/IP domain information



20. Configure TCP/IP applications

21 Configure related tables

22. Configure point-to-point TCP/IP

Which action is necessary for the additional server to be used?

A. Option 10 Add the server to the host table entries and restart TCP

B. Option 2 Add a new route for the new DNS server

C. Option 12 Add the IP address for the DNS server and press Enter

D. Option 22 Add a new Point-to-Point connection for the server

Correct Answer: C

[Latest C9010-030 Dumps](#)

[C9010-030 Study Guide](#)

[C9010-030 Braindumps](#)