



C9510-319^{Q&As}

IBM WebSphere Application Server Developer Tools V8.5 with Liberty Profile

Pass IBM C9510-319 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/c9510-319.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which one of the mechanisms CANNOT be used directly by the JAX-WS dynamic APIs for Dispatch or Provider?

- A. Source
- B. Data Source
- C. Input Stream
- D. JAXB Objects
- E. SOAP Message

Correct Answer: C

QUESTION 2

Which statements below are TRUE in IBM Web Sphere Application Server V7.0?

- A. JAX-WS and JAX-RPC both offer support for SOAP with attachments
- B. JAX-WS only supports MTOM and JAX-RPC only supports SOAP with Attachments.
- C. JAX-RPC supports WSDL 1.1 and SOAP 1.1 only. JAX-WS adds support for both WSDL 2.0 and SOAP 1.2.
- D. JAX-RPC does not validate any SOAP messages. However JAX-WS, with its inclusion of JAXB, validates all SOAP messages.
- E. JAX-WS based Web services add native support for WS-Addressing whereas JAX-RPC only offers Web Sphere-specific APIs to use WS-Addressing.

Correct Answer: AE

QUESTION 3

A developer has created a Liberty server in WebSphere Application Server Developer Tools for Eclipse.

How can the developer start the Liberty server from the Servers view using a JRE different from the default JRE?

- A. Open the Runtime Explorer view, select the runtime and click the Properties context sensitive menu item. Change the JRE setting under the Server category in the Properties dialog.
- B. Open the Server Configuration editor by double clicking the server configuration in the Servers view, add a JVM configuration element and specify the JRE location in the Location field.
- C. Open the Server editor by double clicking the server in the Servers view, select the Runtime Environments link and change the JRE setting in the Liberty Profile Runtime Environment dialog.



D. Open the Server Configuration editor by double clicking the server configuration in the Servers view, add a Variable configuration element with the Name field set to java.home and the Value field set to the location of the JRE.

Correct Answer: C

QUESTION 4

A developer is creating a new Web service from a Java bean.

Which of the following tasks CANNOT be performed using the Create Web Service Wizard in IBM Rational Application Developer V7.5?

- A. Enable MTOM support
- B. Specify custom bindings files
- C. Publish the Web service to a UDDI registry
- D. Associate the Web service project with an EAR
- E. Configure TCP/IP Monitor to monitor SOAP messages

Correct Answer: B

QUESTION 5

A developer runs a servlet from an OSGi web project named CounterWebBundle on a Liberty server and gets the following error message when the doGet method of the servlet is run:

[ERROR] SRVE0777E: Exception thrown by application class

```
\\com.ibm.ws.eba.servlet.CounterServlet.doGet():42\\java.lang.NoClassDefFoundError: javax.naming.InitialContext
```

How should the developer resolve the problem?

- A. Ensure that jndi-1.0 and serverStatus-1.0 are added to the Feature Manager in the server configuration.
- B. Ensure that jndi-1.0 is added to the Feature Manager in the server configuration and the javax.naming package is added to the Import-Package of CounterWebBundle.
- C. Ensure that jndi-1.0 is added to the Feature Manager in the server configuration and Web 2.0 is selected in the Project Facets of the Properties for CounterWebBundle.
- D. Ensure that jndi-1.0 is added to the Feature Manager in the server configuration and the javax.naming.InitialContext is specified in the init-method of the beans specified in the blueprint.xml file of CounterWebBundle.

Correct Answer: B