



CWAP-403^{Q&As}

Certified Wireless Analysis Professional

Pass CWNP CWAP-403 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/cwap-403.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which one of the following is not a valid reason for an AP to fail a STAs association?

- A. Requesting station has the wrong PSK
- B. Does not support the specified authentication algorithm
- C. AP is unable to handle additional associations
- D. Requesting station does not support all the required data rates

Correct Answer: A

QUESTION 2

Which one of the following should be the first step when troubleshooting a WLAN issue?

- A. Identify capture locations
- B. Identify probable causes
- C. Perform an initial WLAN scan and see if any obvious issues stand out
- D. Define the problem

Correct Answer: D

QUESTION 3

Which common feature of a Spectrum Analyzer would be the best to help you locate a non-802.11 interference source?

- A. Max hold
- B. Location filter
- C. Waterfall plot
- D. Device finder

Correct Answer: D

QUESTION 4

What should the To DS and From DS flags be set to in an Association Response frame?

- A. To DS = 0, From DS = 0
- B. To DS = 0, From DS = 1



C. To DS = 1, From DS = 0

D. To DS = 1, From DS = 1

Correct Answer: A

QUESTION 5

As a wireless network consultant you have been called in to troubleshoot a high-priority issue for one of your customers. The customer's office is based on two floors within a multi-tenant office block. On one of these floors (floor 5) users cannot connect to the wireless network. During their own testing the customer has discovered that users can connect on floor 6 but not when they move to the floor 5. This issue is affecting all users on floor 5 and having a negative effect on productivity. To troubleshoot this issue, you perform both Spectrum and Protocol Analysis. The Spectrum Analysis shows the presence of Bluetooth signals which you have identified as coming from wireless mice. In the protocol analyzer you see the top frame on the network is deauthentication frames. On closer investigation you see that the deauthentication frames' source addresses match the BSSIDs of your customers APs and the destination address is FF:FF:FF:FF:FF:FF. What do you conclude from this troubleshooting exercise?

A. The customer should replace all their Bluetooth wireless mice as they are stopping the users on floor 5 from connecting to the wireless network

B. The users on floor 5 are being subjected to a denial of service attack, as this is happening across the entire floor it is likely to be a misconfigured WIPS solution belonging to the tenants on the floor below

C. The customers APs are misbehaving and a technical support case should be open with the vendor

D. The CCI from the APs on the floor 4 is the problem and you need to ask the tenant below to turn down their AP's Tx power

Correct Answer: A

[CWAP-403 PDF Dumps](#)

[CWAP-403 Exam Questions](#)

[CWAP-403 Braindumps](#)