



# CWSP-205<sup>Q&As</sup>

Certified Wireless Security Professional

**Pass CWNP CWSP-205 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/cwsp-205.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Given: WLAN protocol analyzers can read and record many wireless frame parameters.

What parameter is needed to physically locate rogue APs with a protocol analyzer?

- A. SSID
- B. IP Address
- C. BSSID
- D. Signal strength
- E. RSN IE
- F. Noise floor

Correct Answer: D

---

### QUESTION 2

Given: You have implemented strong authentication and encryption mechanisms for your enterprise

802.11 WLAN using 802.1X/EAP with AES-CCMP.

For users connecting within the headquarters office, what other security solution will provide continuous monitoring of both clients and APs with 802.11-specific tracking?

- A. IPSec VPN client and server software
- B. Internet firewall software
- C. Wireless intrusion prevention system
- D. WLAN endpoint agent software
- E. RADIUS proxy server

Correct Answer: C

---

### QUESTION 3

What protocols allow a network administrator to securely manage the configuration of WLAN controllers and access points? (Choose 2)

- A. SNMPv1
- B. HTTPS
- C. Telnet



- D. TFTP
- E. FTP
- F. SSHv2

Correct Answer: BF

---

#### QUESTION 4

Given: ABC Company secures their network with WPA2-Personal authentication and AES- CCMP encryption.

What part of the 802.11 frame is always protected from eavesdroppers by this type of security?

- A. All MSDU contents
- B. All MPDU contents
- C. All PPDU contents
- D. All PSDU contents

Correct Answer: A

---

#### QUESTION 5

For a WIPS system to identify the location of a rogue WLAN device using location patterning (RF fingerprinting), what must be done as part of the WIPS installation?

- A. All WIPS sensors must be installed as dual-purpose (AP/sensor) devices.
- B. A location chipset (GPS) must be installed with it.
- C. At least six antennas must be installed in each sensor.
- D. The RF environment must be sampled during an RF calibration process.

Correct Answer: D

[Latest CWSP-205 Dumps](#)

[CWSP-205 Practice Test](#)

[CWSP-205 Braindumps](#)