



CWSP-206^{Q&As}

CWSP Certified Wireless Security Professional

Pass CWNP CWSP-206 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/cwsp-206.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You have a Windows laptop computer with an integrated, dual-band, Wi-Fi compliant adapter. Your laptop computer has protocol analyzer software installed that is capable of capturing and decoding 802.11ac data. What statement best describes the likely ability to capture 802.11ac frames for security testing purposes?

- A. Integrated 802.11ac adapters are not typically compatible with protocol analyzers in Windows laptops. It is often best to use a USB adapter or carefully select a laptop with an integrated adapter that will work.
- B. Laptops cannot be used to capture 802.11ac frames because they do not support MU-MIMO.
- C. Only Wireshark can be used to capture 802.11ac frames as no other protocol analyzer has implemented the proper frame decodes.
- D. All integrated 802.11ac adapters will work with most protocol analyzers for frame capture, including the Radio Tap Header.
- E. The only method available to capture 802.11ac frames is to perform a remote capture with a compatible access point.

Correct Answer: A

QUESTION 2

What WLAN client device behavior is exploited by an attacker during a hijacking attack?

- A. After the initial association and 4-way handshake, client stations and access points do not need to perform another 4-way handshake, even if connectivity is lost.
- B. Client drivers scan for and connect to access point in the 2.4 GHz band before scanning the 5 GHz band.
- C. When the RF signal between a client and an access point is disrupted for more than a few seconds, the client device will attempt to associate to an access point with better signal quality.
- D. When the RF signal between a client and an access point is lost, the client will not seek to reassociate with another access point until the 120 second hold down timer has expired.
- E. As specified by the Wi-Fi Alliance, clients using Open System authentication must allow direct client-to-client connections, even in an infrastructure BSS.

Correct Answer: C

QUESTION 3

ABC Company is deploying an IEEE 802.11-compliant wireless security solution using 802.1X/EAP authentication. According to company policy, the security solution must prevent an eavesdropper from decrypting data frames traversing a wireless connection. What security characteristic and/or component plays a role in preventing data decryption?

- A. 4-Way Handshake



- B. PLCP Cyclic Redundancy Check (CRC)
- C. Multi-factor authentication
- D. Encrypted Passphrase Protocol (EPP)
- E. Integrity Check Value (ICV)

Correct Answer: A

QUESTION 4

You must implement 7 APs for a branch office location in your organizations. All APs will be autonomous and provide the same two SSIDs (CORP1879 and Guest).

Because each AP is managed directly through a web-based interface, what must be changed on every AP before enabling the WLANs to ensure proper staging procedures are followed?

- A. Output power
- B. Fragmentation threshold
- C. Administrative password
- D. Cell radius

Correct Answer: C

QUESTION 5

Many computer users connect to the Internet at airports, which often have 802.11n access points with a captive portal for authentication. While using an airport hotspot with this security solution, to what type of wireless attack is a user susceptible?

- A. Wi-Fi phishing
- B. Management interface exploits
- C. UDP port redirection
- D. IGMP snooping

Correct Answer: A

[CWSP-206 PDF Dumps](#)

[CWSP-206 Study Guide](#)

[CWSP-206 Exam Questions](#)