



# DEA-5TT1<sup>Q&As</sup>

Associate - Networking Exam

**Pass EMC DEA-5TT1 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/dea-5tt1.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

When configuring a switch, which CLI mode only supports limited show commands?

- A. EXEC
- B. Maintenance
- C. Configuration
- D. EXEC Privilege

Correct Answer: A

Reference: [https://www.dell.com/support/manuals/us/en/04/powerededge-fx2/dell%20fn%20ioa%20config\\_9.8.0.0\\_pub-v1/cli-modes?guid=guid-aeb7d44d-2413-4da8-b8b9-2f8a26bad435&lang=en-us](https://www.dell.com/support/manuals/us/en/04/powerededge-fx2/dell%20fn%20ioa%20config_9.8.0.0_pub-v1/cli-modes?guid=guid-aeb7d44d-2413-4da8-b8b9-2f8a26bad435&lang=en-us)

---

### QUESTION 2

What is the default OSPF "hello interval"?

- A. 5 seconds
- B. 10 seconds
- C. 15 seconds
- D. 30 seconds

Correct Answer: B

### QUESTION 3

Which port type does a Dell EMC Networking N-Series switch have for its console connection?

- A. DB9
- B. RJ-45
- C. USB A
- D. USB B

Correct Answer: A

Reference: [https://downloads.dell.com/manuals/all-products/esuprt\\_ser\\_stor\\_net/esuprt\\_networking/esuprt\\_net\\_fxdprt\\_swch/networking-n3100-series\\_user%27s-guide10\\_en-us.pdf](https://downloads.dell.com/manuals/all-products/esuprt_ser_stor_net/esuprt_networking/esuprt_net_fxdprt_swch/networking-n3100-series_user%27s-guide10_en-us.pdf) page 197

---

### QUESTION 4



What does the switch do with the frame?

- A. Flushes the destination MAC address and updates the MAC address table in the switch.
- B. Adds the source MAC address and port to the MAC address table and forwards the frame.
- C. Discards the frame on all ports and sends an error message back to the host.
- D. Floods the frame to all ports except for the port the frame originated from to locate the source MAC address.

Correct Answer: B

---

#### QUESTION 5

A network administrator has a Dell EMC switch that has been configured with several VLANs. Each VLAN switch virtual interface (SVI) has an IP address assigned to it with each of them on different subnets. In addition, routing has been enabled on the switch.

Which action occurs when the switch receives a packet on one of its SVIs but the destination IP address of the packet does not match the IP address of that SVI?

- A. Switch checks its routing table and forwards the packet accordingly.
- B. Switch duplicates the packet and sends it to all interfaces.
- C. Switch replies back to the source with an ICMP Reject packet.
- D. Switch drops the packet.

Correct Answer: A

[Latest DEA-5TT1 Dumps](#)

[DEA-5TT1 Exam Questions](#)

[DEA-5TT1 Braindumps](#)