



DES-1121^{Q&As}

Specialist - Implementation Engineer PowerMax and VMAX Family
Solutions Version 1.0

Pass EMC DES-1121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-1121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which PowerMax software packages include Non-Disruptive Migration?

- A. FX and Pro
- B. Essentials and Pro
- C. F and FX
- D. F and Essentials

Correct Answer: A

QUESTION 2

A systems administrator asks whether their host is supported for non-disruptive migration (NDM) between PowerMax arrays. The host they plan to migrate has one HBA and no multipathing software. What information should be provided to the administrator?

- A. Install Solutions Enabler on the host
- B. NDM is supported for the host
- C. Upgrade to the latest host HBA driver version
- D. NDM is not supported for the host

Correct Answer: A

QUESTION 3

You have just presented storage to an ESXi server and want to rescan the storage adapter to ensure the server can see the new volume. Based on recommended best practices, what is the preferred method to perform this task?

- A. Use the vSphere VSI plugin to rescan the entire cluster
- B. Run the command from a non-cluster host using the ESX CLI
- C. Use the vSphere Client to perform the rescan of the host
- D. Run the command from the ESXi server with the ESX CLI enabled

Correct Answer: A

QUESTION 4

What are the main options used to complete a configuration change using the synconfigure command?



- A. preview, prepare, commit
- B. preview, prepare, reserve
- C. preview query, reserve
- D. preview query, commit

Correct Answer: A

QUESTION 5

Production work has been started on the R2 devices after an 5RDF Failover operation. Where will the changes made to the R2 devices be reflected in the SRDF Query output shown in the exhibit?

Target (R2) View				Source (R1) View				MODE	
Standard	ST			LI	ST				
Logical	A	T R1 Inv	R2 Inv	N	A	T R1 Inv	R2 Inv	RDF Pair	
Device	Sym	E Tracks	Tracks	K Sym	Sym	E Tracks	Tracks	MACE STATE	
	Dev			S Dev	Dev				
DEV001	00087	1	2	00059	3	4	S...		
DEV002	00088			0005A			S...		

- A. 1
- B. 2
- C. 3
- D. 4

Correct Answer: A

[DES-1121 Study Guide](#)

[DES-1121 Exam Questions](#)

[DES-1121 Braindumps](#)