



DES-4121^{Q&As}

PowerEdge Specialist Exam for Implementation Engineer

Pass EMC DES-4121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-4121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A technician needs to use the iDRAC GUI to roll back a diagnostics firmware revision on a server that was updated four weeks previously. However, the replaced version cannot be found in the Firmware Rollback section on the iDRAC GUI.

What could be the issue?

- A. Diagnostics firmware revision is part of the Lifecycle Controller firmware so the Lifecycle Controller must be updated first
- B. Rollback feature was not enabled in iDRAC Settings
- C. Firmware can only be rolled back within a week of being replaced.
- D. Diagnostics firmware is not supported in the Rollback feature.

Correct Answer: D

QUESTION 2

A technician needs to repurpose a server. What should they do to prepare the server for its new role?

- A. Boot into F10, select System Erase, and press "Y" to confirm erase
- B. Enable Delete All Settings in the iDRAC Troubleshooting section
- C. Boot into F10, navigate to Retire or Repurpose Server, and Select Components to be cleared
- D. Boot to Ctrl+S and perform Network Erase

Correct Answer: B

Reference https://www.dell.com/support/manuals/pk/en/pkbsd1/idrac8-with-lc-v2.05.05.05/lc_2.05.05.05_ug-v1/repurpose-or-retire-system?guid=guid-0239f793-bfa0-4af7-8a47e823356a1aa2&lang=en-us

QUESTION 3

A technician is setting up a previously used server. Upon power up, the PERC alerts them to the presence of a foreign configuration. In the iDRAC storage section, the technician checks Foreign View. The foreign array configuration is the same as the configuration needed for the new project.

What is a recommended way to prepare the disks for the new project?

- A. Edit the foreign configuration and set it to Ready
- B. Import the foreign configuration and perform a full initialization
- C. Format the foreign configuration and clear the controller configuration
- D. Access the Ctrl+R utility, clear the foreign configuration and set up array as needed



Correct Answer: D

Reference <https://www.dell.com/community/PowerEdge-HDD-SCSI-RAID/PERC-H310-active-drives-arelisted-in-foreign-config/td-p/6126153>

QUESTION 4

A server has two power supply units (PSUs) in a redundant configuration. One PSU fails. A technician replaces the failed PSU, but the server does not return to redundant power mode.

What is the cause of this issue?

- A. Power redundant option is disabled in the System Setup Utility.
- B. Server has not been power cycled to bring the new PSU online
- C. Both PSUs were not replaced at the same time
- D. New PSU has a different wattage than the existing PSU

Correct Answer: B

QUESTION 5

A server is equipped with 2 CPUs and 12x 8 GB DIMMs, for a total of 96 GB. The OS is not seeing all the memory. Which memory mode should be configured so that all memory is seen by the OS?

- A. Mirroring
- B. Advanced ECC
- C. Optimizer
- D. Sparing

Correct Answer: C

Reference <https://www.dell.com/support/article/pk/en/pkbsd1/sln155709/memory-modes-in-dualprocessor-11th-generation-powerededge-servers?lang=en#Sparing>

[DES-4121 PDF Dumps](#)

[DES-4121 Practice Test](#)

[DES-4121 Study Guide](#)