



# DES-4121<sup>Q&As</sup>

PowerEdge Specialist Exam for Implementation Engineer

**Pass EMC DES-4121 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-4121.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

A server is configured with a RAID 5 Virtual Disk across five hard disks and one spare disk. If a hard disk failure occurs within the RAID 5 virtual disk, the spare disk needs to be online as quickly as possible. It is acceptable for users to experience decreased performance during the rebuild procedure.

How should this requirement be met?

- A. Enable Rebuild Priority
- B. Increase Rebuild Rate
- C. Change cache to Write Through
- D. Select Fast Rebuild

Correct Answer: A

---

### QUESTION 2

A technician deletes the iDRAC Express license on a R440 server. Which license type is then enabled?

- A. iDRAC Express license cannot be deleted
- B. iDRAC Basic license
- C. iDRAC Enterprise license
- D. iDRAC will not have a license until a new one is installed

Correct Answer: B

---

### QUESTION 3

A technician needs to install the OS on a server remotely using iDRAC. What is the minimum iDRAC license required to perform this task?

- A. Express
- B. Enterprise
- C. Basic
- D. Baseboard Management Controller

Correct Answer: B

Reference <https://community.spiceworks.com/topic/514389-dell-idrac-licensing>

---



---

#### QUESTION 4

A technician needs to connect a server to a network but the network switch has only two available network ports so only two network cables can be connected. The user needs as much bandwidth as possible for their workload so the two network cables need to connect to LOM1 and LOM2. The technician wants to satisfy the user requirements yet still be able to access the iDRAC.

What is the best way to configure the iDRAC?

- A. Use a splitter cable in one of the network switch ports to connect the same cable to both LOM1 and LOM2 with the second network cable connecting to the iDRAC Dedicated NIC
- B. Set up a dedicated NIC with LOM1 as the NIC selection
- C. Use a splitter cable in one of the network switch ports to connect the same cable to both LOM1 and the iDRAC Dedicated NIC
- D. Set up a shared LOM with LOM1 as the NIC selection

Correct Answer: B

---

#### QUESTION 5

A technician plugs in a server that has dual power supply units. After powering on the system, they notice that the power supply status indicators blink green then turn off.

What troubleshooting steps should the technician take to resolve this issue?

- A. Set the power supply redundancy option to 'No Redundancy'
- B. Check that the PSUs are not connected to a 240VAC source
- C. Update the iDRAC firmware to enable control of new PSU features
- D. Check that the PSUs are the same efficiency, feature set, health status, and supported voltage

Correct Answer: D

Reference <https://qrl.dell.com/Files/en-us/Html/Manuals/R630/Power%20indicator%20codes=GUIDFBD2281B-1608-4F8-9AFE-4E33BB6FF810=1=en-us=.html>

[DES-4121 VCE Dumps](#)

[DES-4121 Practice Test](#)

[DES-4121 Study Guide](#)