



# DES-4421<sup>Q&As</sup>

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

## Pass EMC DES-4421 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-4421.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





## QUESTION 1

### DRAG DROP

A datacenter administrator has been tasked to perform firmware updates of the whole chassis and its components based on the latest dell.com catalog.

What is the correct sequence of actions?

Select and Place:

Click Compliance Report	STEP 1
Add a Catalog	STEP 2
Select Target Devices or Groups	STEP 3
Navigate to Configuration > Firmware menu	STEP 4
Create a Baseline	STEP 5

Correct Answer:

	Navigate to Configuration > Firmware menu
	Create a Baseline
	Add a Catalog
	Select Target Devices or Groups
	Click Compliance Report

## QUESTION 2

In the assigned mapping of the MX5016s storage sled what is an assignment option used for independent storage to be mapped to a compute sled?

A. Drive-assigned enables the MX5016s to be split among multiple compute sleds. Each compute node only "sees" the disks that are assigned to it and not the others.

B. Drive-assigned enables the MXG610s to the first eight drives in the MX5016s.



C. Enclosure-assigned enables the MX5016 to be split among multiple compute sleds. Each compute node only "sees" the disks that are assigned to it and not the others.

D. Enclosure-assigned enables the MXG610s to the first eight drives in the MX5016s.

Correct Answer: A

### QUESTION 3

Which I/O module is supported for Fabric B?

A. MX5016s

B. MSG610s

C. MX5000s

D. MX5108n

Correct Answer: D

Reference: <https://hasanmansur.com/2019/01/08/mx7000-networking-part-1-introduction-components/>

### QUESTION 4

What item is used to refer to a daisy-chained configuration of a multiple MX7000 chassis environment?

A. Wired group

B. Identity group

C. Chassis group

D. Physical group

Correct Answer: A

Reference: [https://topics-cdn.dell.com/pdf/openmanage-enterprise-modular-v10010-poweredge-mx7000\\_users-guide4\\_en-us.pdf](https://topics-cdn.dell.com/pdf/openmanage-enterprise-modular-v10010-poweredge-mx7000_users-guide4_en-us.pdf) (23)

### QUESTION 5

A technician replaces a failed Management Module in an MX7000 chassis group. After the technician leaves the site, the administrator reports that the lead chassis is no longer able to communicate with its members. How can OME-M be used to confirm the cabling configuration?

A. View the health status of the lead Chassis Management Module

B. View the health status of the lead Chassis Management ports

C. View the I/O module topology map from the lead chassis



D. View the topology map from the Group Lead

Correct Answer: B

[Latest DES-4421 Dumps](#)

[DES-4421 Study Guide](#)

[DES-4421 Braindumps](#)