



DES-5121^{Q&As}

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-5121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Refer to the Exhibit.

```
Switch-1(config)# radius server host 10.1.1.111 Switch-1(config-radius)# key "secretkey" Switch-1(config-radius)# exit
Switch-1(config)# aaa authentication login "LOCAL-AUTH" local Switch-1(config)# aaa authentication login "REMOTE-
AUTH" radius local Switch-1(config)# aaa authentication enable "REMOTE-AUTH" radius enable Switch-1(config)# aaa
authentication login default tacacs local Switch-1(config)# aaa authentication enable default tacacs enable
Switch-1(config)# line telnet Switch-1(config-telnet)# login authentication "REMOTE-AUTH" Switch-1(config-telnet)# exit
Switch-1(config)# line ssh Switch-1(config-ssh)# login authentication default Switch-1(config)# exit Switch-1(config)# line
console Switch-1(config-line)# login authentication "LOCAL-AUTH" Switch-1(config-line)# exit
```

Which authentication method will be used if a user tries to log into the switch when accessing through SSH?

- A. RADIUS, then fails over to a local user account
- B. Local user account
- C. TACACS, then fails over to a local user account
- D. None

Correct Answer: C

QUESTION 2

Which Layer 3 protocol does MLAG support?

- A. None
- B. Static Routing
- C. OSPF
- D. RIPv2

Correct Answer: A

Reference: http://files.rakurs.su/IT/Kommytatory/Dell/N4000/powerconnect_nx00-usingmlag-whtppr_en-us.pdf

QUESTION 3

You are tasked with deploying a single Dell EMC N-Series switch with a 2-port port-channel to uplink to an existing upstream switch. The following reflects the upstream switch configuration:

```
N4032F#show running-config interface tengigabitethernet 1/0/5 channel-group 1 mode on N4032F#show running-config
interface tengigabitethernet 1/0/6 channel-group 1 mode on
```

Which type of port-channel should be configured to successfully uplink?

- A. Active



- B. MLAG
- C. Static
- D. Passive

Correct Answer: C

QUESTION 4

When setting up VoIP, you decide that you want to use LLDP. LLDP is enabled by default and LLDP Transmit Management Information and Notification modes are enabled.

What additional steps need to be performed?

- A. Enable ISDP and enable LLDP-MED confignotification
- B. Disable ISDP and enable LLDP-MED confignotification
- C. Enable ISDP and disable LLDP-MED confignotification
- D. Disable ISDP and disable LLDP-MED confignotification

Correct Answer: B

QUESTION 5

A user's workstation has an IP phone connected to a Dell EMC N-Series switch.

What is the recommended number of VLANs that should be configured on the switch port?

- A. 0
- B. 1
- C. 2
- D. 3

Correct Answer: C

[Latest DES-5121 Dumps](#)

[DES-5121 PDF Dumps](#)

[DES-5121 VCE Dumps](#)