



DES-5121^{Q&As}

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-5121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which interface on a Dell EMC N-Series switch provides the most security for management?

- A. VLAN
- B. Ethernet
- C. Loopback
- D. Out-of-band

Correct Answer: D

QUESTION 2

After setting up the VoIP configuration, a network administrator issues the following commands with the results shown:

```
console# show voice vlan Administrative Mode.....Enable
```

```
console# show voice vlan it gi 1/0/2
```

```
Interface.....Gi1/0/2
```

```
Voice VLAN Interface Mode.....Enabled
```

```
Voice VLAN ID.....10
```

```
Voice VLAN COS Overwrite.....False
```

```
Voice VLAN DSCP Value.....46
```

```
Voice VLAN Port Status.....Enabled
```

```
Voice VLAN Authentication.....Disabled
```

Based on this information, what is the Layer 3 QoS value?

- A. 5
- B. 10
- C. 46
- D. Gi1/0/2

Correct Answer: C

QUESTION 3

DRAG DROP



What is the typical sequence of steps to upgrade the firmware of a Dell EMC N-Series switch?

Select and Place:

Copy the firmware image from the TFTP server to the switch	Step 1
Configure and start the TFTP server	Step 2
Update the boot code on the switch and reboot	Step 3
Backup the running-config to a TFTP server	Step 4
Select the new image for the next boot	Step 5

Correct Answer:

	Configure and start the TFTP server
	Backup the running-config to a TFTP server
	Copy the firmware image from the TFTP server to the switch
	Select the new image for the next boot
	Update the boot code on the switch and reboot

QUESTION 4

A network has two switches with the following IP addresses:

Switch1: 192.168.1.240



Switch2: 192.168.1.241

The administrator wants to add VRRP on an existing switch configuration using the virtual IP 192.168.1.240.

What is a VRRP requirement for this configuration?

- A. Priority 241 on Switch2
- B. Priority 255 on Switch1
- C. Virtual Router ID 1
- D. Virtual Router ID 240

Correct Answer: B

QUESTION 5

Which AAA method is only used for 802.1x and never returns an error?

- A. local
- B. enable
- C. ias
- D. line

Correct Answer: C

Reference: http://ftp.dell.com/manuals/all-products/esuprt_ser_stor_net/esuprt_networking/powerconnect-8100_concept%20guide2_en-us.pdf page 209

[Latest DES-5121 Dumps](#)

[DES-5121 Study Guide](#)

[DES-5121 Braindumps](#)