



DES-5221^{Q&As}

Specialist Implementation Engineer Data Center Networking Exam

Pass EMC DES-5221 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-5221.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

The network administrator wants to configure RADIUS authentication for VTY access, and for console access to use the local configuration. Which two commands should be used to achieve this goal?

- A. aaa authentication login vty group radius aaa authentication login console local
- B. aaa authentication login default group radius aaa authentication login console local
- C. aaa authentication login vty radius aaa authentication login console group local
- D. aaa authentication login default group radius aaa authentication login console group local

Correct Answer: B

QUESTION 2

Two OS10 switches reside within a VLT domain with statically configured primary-priorities. The current primary peer, switch OS10-A, has a priority of 100, while the secondary peer, OS10-B, has a priority of 200.

If OS10-A reboots and comes back online, what roles will the VLT peers be assigned?

- A. OS10-A will be primary and OS10-B will be secondary.
- B. OS10-A will be secondary and OS10-B will be master.
- C. OS10-A will be standby and OS10-B will be primary.
- D. OS10-A will be secondary and OS10-B will be primary.

Correct Answer: D

QUESTION 3

From which range can a network administrator choose when setting the RSTP priority value?

- A. 1-6400
- B. 0-61440
- C. 0-614400
- D. 1-64

Correct Answer: B

Reference: <https://www.dell.com/support/article/en-my/how10394/how-to-manage-rapid-spanning-tree-rstp-thru-command-line-on-dell-networking-powerconnect-switches?lang=en>



QUESTION 4

How are multiple hardware based ACLs filtered?

- A. NTP
- B. DHCP
- C. NPU
- D. IP

Correct Answer: C

Reference: https://www.dell.com/support/manuals/us/en/04/networking-z9264f-on/os10-enterprise-user-guide-10_4_2-pub/access-control-lists?guid=guid-c220a14f-c6cb-4950-ba88-15cbd59316aa&lang=en-us

QUESTION 5

```
OS10-A# show vrrp 100
```

```
Interface           : vlan100           IPv4 VRID           : 100
Version             : 2                   State                : master-state
Primary IP          : 10.0.100.1         Master IP            : 10.0.100.2
Virtual MAC         : 00:00:5e:00:01:64   Accept Mode         : true
Admin Priority       : 110                Operational Priority : 110
Advertise Interval  : 1                   Hold Time            : 0
(in secs)

Preempt Status      : false
Virtual IP address  : 10.0.100.1

master-transitions  : 1                   advertise-rcvd      : 2
advertise-interval-errors : 0         ip-ttl-errors       : 0
priority-zero-pkts-rcvd : 0         priority-zero-pkts-sent : 0
invalid-type-pkts-rcvd  : 0         address-list-errors  : 0
pkt-length-errors     : 0
```

Refer to the exhibit.

What is the VRRP state of OS10-A after a router with a default VRRP admin priority with VRID100 comes online?

- A. master-state
- B. standby-state
- C. backup-state
- D. primary-state

Correct Answer: A

[Latest DES-5221 Dumps](#)

[DES-5221 PDF Dumps](#)

[DES-5221 Practice Test](#)