



DES-6322^{Q&As}

Specialist - Implementation Engineer-VxRail Exam

Pass EMC DES-6322 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/des-6322.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

DRAG DROP

Match each VxRail data protection solution with its functionality.

Select and Place:

<u>Solution:</u>	<u>Functionality:</u>
PowerProtect	Site protection and failover
Stretched Cluster	Asynchronous replication for VMs
RecoverPoint for VM	Built-in cloud tiering to send data to the cloud
vSphere Replication	Synchronous and asynchronous VM replication

Correct Answer:

<u>Solution:</u>	<u>Functionality:</u>
	Stretched Cluster
	vSphere Replication
	PowerProtect
	RecoverPoint for VM

Reference: <https://www.vmware.com/products/vsphere/replication.html>

<https://volumes.blog/2020/08/31/rp4vms53/>

<https://infohub.delltechnologies.com/l/techbook-dell-emc-vxrail-system-2/data-protection-82#:~:text=Protecting%20VM%20workloads%20on%20VxRail%20clusters%20can%20be%20achieved%20with%20various%20options.andtext=Stretched%20clusters%20are%20a%20native,in%20case%20of%20site%20failures>

QUESTION 2

What is the correct CLI command to collect only the vCenter logs on VxRail Manager?

A. vc-support.sh -v



B. generateFullBundle.py -v

C. vc-support-bundle.sh -c

D. generateLogBundle.py -c

Correct Answer: D

Reference: <https://davidring.ie/2021/01/14/vxrail-7-0-useful-log-file-information/>

QUESTION 3

DRAG DROP

What is the correct sequence of steps to perform a RASR Factory Reset using an SD card?

Select and Place:

Boot the node from the internal SD card	Step 1
Acknowledge the Warning and Caution messages, then type "Disconnected" to proceed	Step 2
Access iDRAC and launch virtual console to the VxRail node	Step 3
Quit the RASR menu and reboot the system	Step 4
Select F – Factory Reset in the RASR Menu	Step 5

Correct Answer:



	Access iDRAC and launch virtual console to the VxRail node
	Quit the RASR menu and reboot the system
	Acknowledge the Warning and Caution messages, then type "Disconnected" to proceed
	Boot the node from the internal SD card
	Select F – Factory Reset in the RASR Menu

QUESTION 4

Which VxRail Series is designed to support a VDI environment and requires a GPU card in each host?

- A. S Series
- B. V Series
- C. G Series
- D. P Series

Correct Answer: A

Reference: <https://www.arrow.com/ecs-media/13768/h18599-vdi-and-ai-in-healthcare-reference-architecture.pdf>

QUESTION 5

A systems engineer needs to ensure that the VxRail system is healthy and any issues found are addressed prior to starting an upgrade process. Where in the vSphere Client can they review alarms and overall vSAN health?



A. Triggered Alarms > Issues and Alarms > All issues Triggered Alarms > vSAN > Skyline Health

B. Monitor > All Issues > Issues and Alarms Monitor > vSAN > Health

C. Triggered Alarms > All Issues > Issues and Alarms Triggered Alarms > vSAN > Health

D. Monitor > Issues and Alarms > All issues Monitor > vSAN > Skyline Health

Correct Answer: B

[Latest DES-6322 Dumps](#)

[DES-6322 Practice Test](#)

[DES-6322 Exam Questions](#)