



E22-258^{Q&As}

XtremIO 3.x Flash Storage Solutions

Pass EMC E22-258 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/e22-258.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

When deploying an ESRS IP Client solution, which software component should be installed on the XtremIO Management Server (XMS)?

- A. DC Agent
- B. FTPS
- C. DNS
- D. NTP

Correct Answer: A

QUESTION 2

An XtremIO storage array reports an overall efficiency of 30:1. Which combination of Deduplication Ratio (DR), Compression Ratio (CR), and Thin Provisioning Saving (TPS) would achieve this efficiency?

- A. DR = 2.5:1; CR = 4.0:1; TPS = 30%
- B. DR = 3.0:1; CR = 2.0:1; TPS = 50%
- C. DR = 4.0:1; CR = 2.5:1; TPS = 70%
- D. DR = 5.0:1; CR = 2.0:1; TPS = 66%

Correct Answer: D

QUESTION 3

XtremIO storage is assigned to a host. If the host has the HBA execution throttle set to 256, what effect will this have on the system?

- A. Queue depth for each HBA port will be set to 256
- B. Each LUN visible to the port will have a queue depth set to 256
- C. Aggregate queue depth for all HBA ports will be set to 256
- D. Each LUN visible to the port will have a queue depth set to 256 /

Correct Answer: A

QUESTION 4

What accurately describes a use case for Database/Analytic environments?



- A. High, small block random I/O activity. Application environments that require very low and consistent response times.
- B. Low, small block random I/O activity. Application environments that tolerate high response times.
- C. High, large block sequential I/O activity. Application environments that require very low and consistent response times.
- D. Low, small block sequential I/O activity. Application environments that requires very low and consistent response times.

Correct Answer: A

QUESTION 5

Which three performance parameters can be monitored using the XtremIO GUI?

- A. Bandwidth, IOPS, Latency
- B. Bandwidth, IOPS, Utilization
- C. Utilization, IOPS, Service Time
- D. Latency, Bandwidth, Response Time

Correct Answer: A

[E22-258 PDF Dumps](#)

[E22-258 VCE Dumps](#)

[E22-258 Braindumps](#)