



# EX407<sup>Q&As</sup>

Red Hat Certified Specialist in Ansible Automation exam

## Pass RedHat EX407 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ex407.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by RedHat  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which is the default inventory file used by Ansible?

- A. `/${PWD}/.inventory`
- B. `/etc/hosts`
- C. `/etc/ansible/inventory`
- D. `/etc/ansible/hosts`

Correct Answer: D

Ansible refers to `/etc/ansible/hosts` as the default inventory.

---

### QUESTION 2

What formats may variables specified on the command line use when not using a file with the `-e` flag? (Choose all that apply.)

- A. YAML
- B. CSV
- C. Ansible dictionary
- D. JSON

Correct Answer: AD

Variables must be specified in JSON format when passed via command line.

---

### QUESTION 3

In `/home/sandy/ansible/create` a playbook called `logvol.yml`. In the play create a logical volume called `lv0` and make it of size `1500MiB` on volume group `vg0`. If there is not enough space in the volume group print a message "Not enough space for logical volume" and then make a `800MiB` `lv0` instead. If the volume group still doesn't exist, create a message "Volume group doesn't exist". Create an `xf`s filesystem on all `lv0` logical volumes. Don't mount the logical volume.

Correct Answer:

See the for complete Solution below. Solution as:



```
- name: hosts
hosts: all
tasks:
- name: create partition
parted:
  device: /dev/vdb
  number: 1
  flags: [ lvm ]
  state: present
- name: create vg
lvg:
  vg: vg0
  pvs: /dev/vdb1
when: ansible_devices.vdb.partitions.vdb1 is defined
- name: create logical volume
lvol:
  vg: vg0
  lv: lv0
  size: 1500m
when: ansible_lvm.vgs.vg0 is defined and ((ansible_lvm.vgs.vg0.size_g | float) > 1.5)
- name: send message if volume group not large enough
debug:
  msg: Not enough space for logical volume
when: ansible_lvm.vgs.vg0 is defined and ((ansible_lvm.vgs.vg0.size_g | float) < 1.5)
- name: create a smaller logical volume
lvol:
  vg: vg0
  lv: lv0
  size: 1500m
when: ansible_lvm.vgs.vg0 is defined and ((ansible_lvm.vgs.vg0.size_g | float) < 1.5)
- name: create fs
filesystem:
  dev: /dev/vg0/lv0
  fstype: xfs
when: ansible_lvm.vgs.vg0 is defined
```



#### QUESTION 4

What does the when keyword do?

- A. There is no when keyword
- B. Allows a task to be conditional
- C. Allows a play to be conditional
- D. Allows a play to be scheduled

Correct Answer: B

---

#### QUESTION 5

What keyword stores a command's output into a variable?

- A. register
- B. output
- C. output is stored in a variable named results by default
- D. debug

Correct Answer: A

The register keyword will store output from the preceding command into a provided variable.

[EX407 VCE Dumps](#)

[EX407 Study Guide](#)

[EX407 Braindumps](#)