



EX447^{Q&As}

Red Hat Certified Specialist in Advanced Automation: Ansible Best Practices

Pass RedHat EX447 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.geekcert.com/ex447.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by RedHat Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

CORRECT TEXT

Create a jinja template in `/home/sandy/ansible/` and name it `hosts.j2`. Edit this file so it looks like the one below. The order of the nodes doesn't matter. Then create a playbook in `/home/sandy/ansible/calledhosts.yml` and install the template on dev node at `/root/myhosts`

```
127.0.0.1 localhost localhost.localdomain localhost4 localhost4.localdomain4
::1 localhost localhost.localdomain localhost6 localhost6.localdomain6

10.0.2.1 node1.example.com node1
10.0.2.2 node2.example.com node2
10.0.2.3 node3.example.com node3
10.0.2.4 node4.example.com node4
10.0.2.5 node5.example.com node5
```

A. See the for complete Solution below.

Correct Answer: A

Solution as:

in `/home/sandy/ansible/hosts.j2`

```
{%for host in groups['all']%}
{{hostvars[host]['ansible_default_ipv4']['address']}} {{hostvars[host]['ansible_fqdn']}}
{{hostvars[host]['ansible_hostname']}}
{%endfor%}
```

in `/home/sandy/ansible/hosts.yml`

```
- name: use template
  hosts: all
  template:
    src: hosts.j2
    dest: /root/myhosts
  when: "dev" in group_names
```



QUESTION 2

CORRECT TEXT

Create a playbook that changes the default target on all nodes to multi-user.target. Do this in a playbook file called target.yml in /home/sandy/ansible

A. See the for complete Solution below.

Correct Answer: A

-

```
name: change default target
```

```
hosts: all
```

```
tasks:
```

-

```
name: change target
```

```
file:
```

```
src:/usr/lib/systemd/system/multi-user.target dest: /etc/systemd/system/default.target state:
```

```
link
```

QUESTION 3

CORRECT TEXT

Create a playbook called timesync.yml in /home/sandy/ansible using the rhel system role timesync. Set the time to use currently configured ntp with the server 0.uk.pool.ntp.org. Enable burst. Do this on all hosts.

A. See the for complete Solution below.

Correct Answer: A

Solution as:

```
- name: use rhel system role
hosts: all
roles:
  - rhel-system-roles.timesync
timesync_ntp_servers:
  - hostname: 0.uk.pool.ntp.org
  iburst: yes
```



QUESTION 4

CORRECT TEXT

Using the Simulation Program, perform the following tasks:

Ad-Hoc Ansible Commands (Number Two) Task:

1. Use the ad-hoc command to make sure php is installed.

2.

Use the ad-hoc command to make sure that php is installed and is the latest version.

3.

Use the ad-hoc command to make sure that httpd is installed.

4.

Use the ad-hoc command to remove httpd from the servers.

A. See the for complete Solution below.

Correct Answer: A

1.

```
ansible all -b -m yum -a '\name=php state=present\'
```

2.

```
ansible all -b -m yum -a '\name=php state=latest\'
```

3.

```
ansible all -b -m yum -a '\name=httpd state=latest\'
```

4.

```
ansibleall -b -m yum -a '\name=httpd state=absent\'
```

QUESTION 5

CORRECT TEXT

Using the Simulation Program, perform the following tasks:

Static Inventories Task:

1.

Add a new group to your default ansible host file. call the group [ec2]

2.



Add a newhost to the new group you created.

3.

Add a variable to a new host entry in the `/etc/ansible/hosts` file. Add the following. `localhost http_port=80 maxRequestsPerChild=808`

4.

Check to see if `maxRequestsPerChild` is pulled out with an ad-hoccommand.

5.

Create a local host file and put a target group and then a host into it. Then ping it with an ad-hoc command.

A. See the for complete Solution below.

Correct Answer: A

1.

Edit the `/etc/ansible/hosts` file. Add a group.

2.

Edit the `/etc/ansible/hosts` file. Add a user under the group you created.

3.

Edit the `/etc/ansible/hosts` file. Find a host. if we add a variable called `maxRequestsPerChild` to the host it would look like this. `host1 maxRequestsPerChild=808`

4.

```
ansible ec2 -m shell -a "echo {{ maxRequestsPerChild }}"
```

5.

Edit a local file. It could be called anything. Lets call it `myhosts`. Inside the file it would have a host like the following. `[mygroup] myusername1.mylabserver.com`

[EX447 PDF Dumps](#)

[EX447 VCE Dumps](#)

[EX447 Practice Test](#)