H12-222 Q&As

HCIP-Routing & Switching-IENP V2.5

Pass Huawei H12-222 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.geekcert.com/h12-222.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

QUESTION 1

Which of the following command is used to configure remote port mirroring on a Huawei router to send the packets mirrored on the remote mirrored port to the monitoring device through the Layer 3 IP network?

A. mirror-sever destination-ip 10.1.0.1 source-ip 192.168.1.1

B. monitor-sever destination-ip 10.1.0.1 source-ip 192.168.1.1

C. observe-sever destination-ip 10.1.0.1 source-ip 192.168.1.1

D. sever destination-ip 10.1.0.1 source-ip 192.168.1.1

Correct Answer: D

QUESTION 2

When configuring source NAT with no-pat configuration parameters, which of the following statements is true?

A. Only the source IP address is translated.

B. Only the destination IP address is translated.

C. The source IP address and source port number are both translated.

D. The destination IP address and destination port number are both translated.

Correct Answer: A

QUESTION 3

What is the broadcast domain of VXLAN called?

A. Broadcast domain

B. Switching domain

C. Bridge domain

D. VLAN domain

Correct Answer: C

QUESTION 4

Which of the following statements regarding the ingress node in MPLS forwarding process are correct? (Multiple Choice)

A. After receiving a data packet, the ingress node searches for tunnel ID in the ILM table first.

B. The ingress node finds the NHLFE entry matching the tunnel ID in the ILM table to associate LFIB and NHLFE entries.

C. The ingress node checks the NHLFE entry to obtain the outbound interface, next hop, outgoing label, and label operation type.

D. The label operation type is Push.

E. The ingress node adds the obtained label to the IP packet, processes EXP by QoS policy, processes the TTL, and forwards the encapsulated MPLS packet to the next hop.

Correct Answer: CD

QUESTION 5

eSight single-server mode allows login of only one user. If another user logs in, the system displays a message indicating that a user is online currently.

A. TRUE

B. FALSE

Correct Answer: B

H12-222 VCE Dumps H12-222 Practice Test H12-222 Study Guide